

Survey No. , Section 6, Town 34 South, Range 16

Survey No. , Section 6, Town 34 South, Range 16



NOTE.—SCALE.....CHAINS TO THE INCH IS USED IN THIS DIAGRAM.
This diagram to be used in platting either one, four or sixteen sections. When used for one section only, scale No. 1 applies; for four sections, scale No. 2; and for sixteen sections, scale No. 3.
General Statutes 1892, § 1500: "And no diagram shall be constructed to scale less than one inch to twenty chains."

This is to certify that I S. L. Hibbard County Surveyor of Montgomery County Kansas, was ordered by Henry Walsing to survey and subdivide Sec. 6, T. 34 R. 16 E. This order was given December 23rd 1893, in connection with the Bleeding Survey. On Feb. 10th 1894 the following named parties were notified that a survey of the above described section would begin on Feb. 20th 1894. (See below) On February 20th 1894, I began the survey. R. F. Holden + Joseph Perry, were selected as chainmen. And with duly sworn, I met to the N. E. corner of Sec. 36, T. 33 R. 15 E. ran with 5280 ft. then stake as temporary corner to Sec. 6, I then ran with 1328 ft. to the stake at a temporary cor. to Sec. 6. At a point 2645' south of the 1/4 post on the East line of Sec. 36, T. 33 R. 15 E. I set a sand stone 19" x 12" x 6" marked 1111. As the North West corner of Sec. 6, T. 34 R. 16 E. Having located this corner & concluded to survey Sec. 36, T. 33 R. 15 E. first, the last named parties, subdivision was completed on Feb. 21st 1894. On Feb. 22nd 1894 I continued the survey on Sec. 6, T. 34 R. 16 E. R. F. Holden and M. J. Shirley were chosen as chainmen and were duly sworn. From N. W. corner Sec. 6, T. 34 R. 16 E. ran with on the Range line at 1323 ft. then at 2643 ft. down stake as temporary 1/4 post on West line Sec. 6. At 5283 ft. found the S. W. corner of Sec. 6, same stone, from S. W. corner of Sec. 6, T. 34 R. 16 E. & ran S. 89° 25' E. at 2640 ft. down stake as temporary, to corner at 5280 ft. down stake as temporary S. E. corner of Sec. 6 & then went East 1/2 mile finding No Sec. corner standing. & then with found the 1/4 post standing on the East line Sec. 7, T. 34 R. 16 E. Measured North from this stone at 2640 ft. down stake which was 18 ft. North of stake set by E. W. Run. Then I set a sand stone 30" x 12" x 8" marked 1111. Went to the 1/4 post on South line Sec. 6 connected it 9 ft. North. Then I set a sand stone 24" x 12" x 6" marked 1111. From S. E. corner Sec. 6 ran North 20' E. at 2640 ft. down stake as temporary 1/4 corner East line Sec. 6. At 5280 ft. down stake as temporary N. E. corner to Sec. 6. I then went to the 1/4 post between Sec. 5 + 32 which I found standing ran N. 89° 35' W. at 2640 ft. down stake 16 ft. West & 3 ft. North of the stake set by N. + South run then down stake as permanent cor. Feb. 23rd 1894, I began at the N. W. corner Sec. 6, T. 34 R. 16 E. ran S. 89° 45' E. at 2640 ft. down stake as temporary cor. 1/4 post at 5282 ft. stake as permanent corner. Then I set a sand stone 24" x 10" x 8" marked 1111. For N. E. corner of Sec. 6, T. 34 R. 16 E. At a point 2640 ft. West on Sec. line from the corner & set a sand stone 25" x 10" x 5" marked 1/4 for 1/4 post North line Sec. 6. Connected S. E. corner with N. E. corner by straight line at a point 2640 ft. North of S. E. corner Sec. 6. I set a sand stone 26" x 12" x 7" marked 1/4 for 1/4 post on East line of Sec. 6. At a point 2640 ft. North of S. W. corner Sec. 6, on Range line I set a sand stone 22" x 9" x 6" marked 1/4 for 1/4 post West line Sec. 6. I connected 1/4 posts by straight line at their intersection & set a sand stone 18" x 10" x 6" marked XX for center Sec. 6. At a point midway between the center of the section and the 1/4 post on the East line of Sec. 6. I set a sand stone 22" x 12" x 6" marked X. For the N. E. corner of Sec. 6, at a point midway between the center of the section and the 1/4 post on the South line of Sec. 6. I set a sand stone 18" x 9" x 5" marked X. For S. W. corner N. W. 1/4 S. E. 1/4 Sec. 6 also set a sand stone 30" x 12" x 8" marked X. 80 rods South of N. E. corner of N. W. 1/4 S. E. 1/4 Sec. 6, at S. E. corner of N. W. 1/4 S. E. 1/4 Sec. 6, T. 34 R. 16, this completed the survey.

NOTICE—Surveyor's Permanent Record, State of Kansas.
(Copyright, 1891, by R. A. Baker, Topeka, Kansas.)
Independence, Kansas, Feb. 10 1894.
You are hereby notified that, at 9 o'clock A. M., on the 20 day of Feb. 1894, I will begin a survey on Section 6, Town 34 South, Range 16, in which you are interested, and shall continue the same from day to day until completed. Commencing at the N. W. corner of said Section, I shall permanently establish
S. L. Hibbard, County Surveyor,
Montgomery County, State of Kansas.

of the N. W. 1/4 S. E. 1/4 Sec. 6, at a point midway between the center of the section and the 1/4 post on the South line of Sec. 6. I set a sand stone 18" x 9" x 5" marked X. For S. W. corner N. W. 1/4 S. E. 1/4 Sec. 6 also set a sand stone 30" x 12" x 8" marked X. 80 rods South of N. E. corner of N. W. 1/4 S. E. 1/4 Sec. 6, at S. E. corner of N. W. 1/4 S. E. 1/4 Sec. 6, T. 34 R. 16, this completed the survey.

Parties notified Feb. 10th 1894,
Henry Walsing
John Walsing
Watson Stewart (pl. fullmer H. M.)
Geo. Boyd,
Henry Messel,
Mrs. Bith Bunning, Mrs. Smith
James Munnell B. Blesing (pl.)
James Ott,
Herman S. Messel,
Mary Smith,
Theodore Sack,
John Bunning,
Anderson Turnbull,
Francis L. Robbins,
G. D. Cherry,
John D. Hillman,
W. E. Allen,
J. E. Maxwell,
George Gilmore (pl.)
E. J. Moore

Var. 8° 50' E.
dated March 8th 1894.
Independence, Montgomery Co., Kansas.
S. L. Hibbard,
Co. Surveyor.