

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I S. L. Hibbard, County Surveyor of Montgomery Co., Kansas was ordered by J. C. Page to survey and subdivise Section 35, Township 33, Range 16, East. On March 9<sup>th</sup> 1895 the following named parties were notified that a survey of the above described section would be made on March 18<sup>th</sup> 1895. J. C. Page, A. J. Fleming, Rodell Foster, S. C. Chaney, A. F. Little, William M. Grogan (agent for Section), R. T. Selby, W. H. Felts, Warren Miller, Minnie Crockett, J. J. Clay, R. H. Reed, C. C. Loyton, Buckeye City, Ohio. On March 18<sup>th</sup> 1895 I began the survey. J. J. Selby and Edgar Brown were selected as chainmen, J. J. Clay as flag man and were duly sworn. I began at the South East Corner of Section 35, T. 33, R. 16, E. a monument stone on the Township line, I ran North 89°30' W. at 1320' down stake at 2640' down stake at 3960' down stake at 5280' ft. Corned out 8 ft. South of the Government Corner stone which I found standing. I connected stake set as temporary corner arm of the 1/4 post south line Sec. 35. 12 ft. West and 14 ft. North as true points for the 1/4 post. From the S.W. Corner Section 35 a monument stone ran north at 2640 ft. down stake in center of Cress road as temporary 1/4 post on west line of Sec. 35 at 5280 ft. down stake over the end of a hedge as temporary N.W. Corner sec. 35. From this temporary N.W. Corner I ran S. 89°35' E. on line parallel with Township line at 1600 ft. boundary river at 2603 ft. found monument 1/4 post on North line of Sec. 35. 35 ft. North of the boundary line. I found witness trees according to Gov. field note for the location of this stone. I continued all the boundary line at 5242 ft. down stake as temporary N.E. Corner Sec. 35. I then went to the S.E. Corner Sec. 35, the Gov. Corner and ran North at 240 ft. boundary River bank (high) River 210 ft. at 1030' offset 100 ft. East at 2648 ft. set back 100 ft. West from over 24 ft. West of a stone the 1/4 post on the East line sec. 35. From this 1/4 post I ran N. 0°10' E. at 2640 ft. down stake as temporary N.E. Corner Sec. 35. I then went to the North East Corner of Sec. 26, T. 33, R. 16, E. on miles with from the Corner of this section as stone I ran South at 5280 ft. Corned out 14 ft. South of stake made by the Run North from the 1/4 post on East line Sec. 35. I divided the distance, and set a line stone 30"x8"x5" marked 1111 as corner to Secs. 25, 26, 35 and 36. From the 1/4 post (corner stone) on the East line of Sec. 35. I ran West as the stake on the West line of Sec. 35. Could be seen where 1/4 post was to be permanently located. I ran on this line to the flag on that stake at 180' boundary River 165 ft. wide at 500 ft. top of West bank of the river at 660 ft. down stake at 1320 ft. down stake at 2640' down stake on E. & W. 1/4 line as temporary center stake. I then went to the 1/4 post on the North line of sec. 35 and ran S. 0°15' E. at 685 ft. boundary River (150 ft. wide) at 2593 ft. 1/4 line E. & W. Corned out 4 ft. East of temporary 1/4 post down temporary stake. I ran South 15' E. at 1320' Corned out 8 ft. West of 1/4 Corner. Connection for the center of the section point would be 4 ft. East of the temporary stake as center of the section made by the North & South run. I connected center and set a line stone 36"x12"x8" marked XX as the center of section 35. At a point 1326 ft. East of the South West Corner sec. 35 set a line stone 20"x8"x8" marked X as the S.E. Corner S.W. 1/4 S.W. 1/4 Sec. 35. At a point 2640 ft. North as the S.E. Corner S.W. 1/4 S.W. 1/4 Sec. 35. At a point 2640 ft. North

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.  
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. B. Bailey, Topeka, Kansas.)

Independence, Kansas, March 9<sup>th</sup> 1895.

You are hereby notified that, at 12 o'clock A. M., on the 18 day of March, 1895, I will begin a survey on Section 35, Town 33, South, Range 16, in which you are interested, and shall continue the same from day to day until completed. Commencing at the S.E. Corner corner of said Section, I shall permanently establish

S. L. Hibbard, County Surveyor,  
Montgomery County, State of Kansas.

of the South West Corner of Sec. 35 set a limestone 22"x17"x9" marked 1/4 as the 1/4 post on the West line of sec. 35. At a point 5280 ft. North of the S.W. Corner Sec. 35. Set a sand stone 16"x8"x6" marked 1111 as the corner to Secs. 26, 27, 34 and 35. Distances from 1/4 line on West line Sec. 35 to center Sec. 35 is 2623 ft. At a point 1316 ft. East of center of Sec. 35. Set a limestone 16"x10"x4" marked X. From this stone run South at 660' down stake at 1320' down stake at 2640' Sec. 35. At a point 1326 ft. West on Sec. line from S.E. Corner Sec. 35 set a sand stone 24"x15"x6" marked X as S.W. Corner S.E. 1/4 S.E. 1/4 Sec. 35. For the 1/4 post on the South line Sec. 35 set a line stone 34"x17"x7" marked 1/4. At a point 1326 ft. West at 1323 ft. North of the S.E. Corner Sec. 35. Set a sand stone 22"x12"x5" marked X as the N.W. Corner S.E. 1/4 S.E. 1/4 Sec. 35. At a point 662 ft. North of the last named corner set a sand stone 19"x15"x8" marked X as N.W. Corner S.W. 1/4 S.E. 1/4 Sec. 35. Also set a stone at the South West Corner of the last described tract of land also set a witness stone 10 ft. West of the true Corner of the South East Corner of the N. 1/2 N.E. 1/4 N.E. 1/4 Sec. 35, T. 33, Range 16 East. This completes the survey March 21, 1895.

Var, 8°35' E.

Witnessed at Independence Montgomery Co. Kansas  
April 20<sup>th</sup> 1895.

S. L. Hibbard,  
Co. Surveyor.

51  
66  
306  
306  
33.66

58  
66  
348  
348  
372.8