

Geo. W. Crane & Co., Topeka, Kas.

The survey of Section 3 continued as notified on Page 43. of This Book, as ordered on May 13th 1895. On May 27, 1895 I began the survey of Section 3, Township 33, Range 16, East. Edgar Wilson, and Adam Swartz were retained as Chainmen and Jacob Betts as Flagman. I began at the South East Corner of Section 3. (A stone) and ran N. 0° 45' W. at 1250 ft. Verdigris River 188 ft. wide by measurement at 2640 ft. down stakes as temporary 1/4 post on East line sec. 3. From this temporary 1/4 post I ran North 0° 45' W. at 2670 ft. down stakes as temporary N.E. Corner sec. 3. I went to a stone at the N.E. Corner of Section 2, T. 33 R. 16 on Township line and ran West on Township line 5268 ft. to the stake set as temporary N.E. Corner of sec. 3. From this temporary N.E. Corner of Section 3 I ran West on Township line between sections 3+34 at 2640 ft. down stakes as temporary 1/4 post on North line section 3. at 5280 ft. down stakes as temporary N.W. Corner sec. 3. The stone at the North West Corner of Section 3 was not to be found. I went to the South West Corner (a stone) of Section 3, and ran N. 0° 35' W. at 2640 ft. down a stake as temporary 1/4 post on West line of Section 3. At 845 ft. N. 0° 35' W. from this temporary 1/4 post the Verdigris River, 190 ft. wide by measurement, at 2640 ft. came out 5 ft. West of the stake set as temporary N.W. Corner of Sec. 3, located by the East and West runs. I corrected this temporary corner 5 ft. West as true corner to Sections 3+4, 33+34. also corrected temporary 1/4 post North line section 3. 5 ft. West, also corrected temporary N.E. Corner sec. 3. 5 ft. West. Set a lime stone 40"x12"x8" marked 1111 in N.E. Corner sec. 3. Corrected 1/4 post East line Sec. 3. 2 1/2 ft. West then I set a lime stone 36"x12"x8" marked 1/4 in the Quarter post on the East line Section 3. I also set a witness stone on the North bank of the Verdigris River 158 ft. North on the section line joining the true corner which falls in the River witness stone a lime stone 18"x4"x6" marked X. From the 1/4 post on the East line section 3. I ran West on the 1/4 line at 1320 down stake as temporary N.W. Corner to N.E. 1/4 S.E. 1/4 Sec. 3. at 2658 ft. fence run, N + South through Sec. 3. then I down stakes as temporary Center section 3. From this temporary Center section 3. I ran West on 1/4 line at 817 ft. water edge of Verdigris River which was 487 ft. wide by measurement at 2645 ft. came out 3 ft. North of temporary 1/4 post on West pile at the point located as 1/4 post on West line section 3. I located as the true point for 1/4 Corner 2 1/2 ft. East. Then I set a lime stone 18"x10"x6" marked 1/4 in the 1/4 post on the West line of Section 3. Also reset old found 1/4 post which I found in the well a flag stone 40"x12"x3" marked 1/4. From a stone the 1/4 post on the South line of Section 3. I ran N. 0° 40' W. at 2045 ft. down stake on South bank of river 20 ft. from water edge measured river 230 ft. wide at 2640 ft. down stake as temporary Center which was 15 ft. West of 1/4 line as I was obliged to set 15 ft. West of true line on account of river fence. Thence North 0° 40' W. from temporary Center at 2651 ft. came out 18 ft. West correction for Center at 1 1/2 ft. East. At a point 2640 ft. on West on Sec. line from N.E. Corner Sec. 3. I set a lime stone 24"x12"x8" marked 1/4 in the 1/4 post on North line sec. 3. At the North West Corner Sec. 3. I set a lime stone 31"x12"x4" marked 1111 for corner to sec. 3, 4, 33+34. At the Center Sec. 3. 1 1/2 ft. East of Corner (temporary) made by N + S run I set a lime stone 32"x12"x6" marked XX, as Center sec. 3. At a point 345 ft. South on 1/4 line on North bank of the Verdigris River set a found stone as witness to line 16"x6"x5" marked X. At a point 1332 ft. West on 1/4 line from the 1/4 post on the East line of Section 3. I set a lime stone 30"x12"x4" marked X as N.W. Corner N.E. 1/4 S.E. 1/4 section 3. Thence South from East corner on a line parallel with the East line of Section 3. 925 ft. I set a lime stone 24"x12"x6" marked X on North bank of the Verdigris River and on the West line of the N.E. 1/4 S.E. 1/4 Sec. 3. at 920 ft. water edge measured the River to a stake South bank 40 ft. at 1320 ft. set a flag stone for S.W. Corner N.E. 1/4 S.E. 1/4 Sec. 3, T. 33 R. 16, E. This completed the survey of Section 3 on May 27, 1895. -

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 189.....

M.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

..... County Surveyor,
..... County, State of Kansas.

Thence (3) set a lime stone 31"x12"x4" marked 1111 for corner to sec. 3, 4, 33+34. At the Center Sec. 3. 1 1/2 ft. East of Corner (temporary) made by N + S run I set a lime stone 32"x12"x6" marked XX, as Center sec. 3. At a point 345 ft. South on 1/4 line on North bank of the Verdigris River set a found stone as witness to line 16"x6"x5" marked X. At a point 1332 ft. West on 1/4 line from the 1/4 post on the East line of Section 3. I set a lime stone 30"x12"x4" marked X as N.W. Corner N.E. 1/4 S.E. 1/4 section 3. Thence South from East corner on a line parallel with the East line of Section 3. 925 ft. I set a lime stone 24"x12"x6" marked X on North bank of the Verdigris River and on the West line of the N.E. 1/4 S.E. 1/4 Sec. 3. at 920 ft. water edge measured the River to a stake South bank 40 ft. at 1320 ft. set a flag stone for S.W. Corner N.E. 1/4 S.E. 1/4 Sec. 3, T. 33 R. 16, E. This completed the survey of Section 3 on May 27, 1895. -

For, S.E. East,

Dated at Independence Montgomery County Iowa 28th 1895.

L. L. Hubbard,
Co. Surveyor.