

Survey No. , Section 11, Town 33, South, Range 16

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I L. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by Thomas W. Hill to survey and subdivide Section Eleven (11), Township 33, Range 16, East, November 11th 1895. The following named parties were notified that a survey of the above described Section would be made on November 19th 1895: John Hunkin, William Hunkin, Caleb Fogel, Tom W. Hill, Daniel W. Taggart, George Brooks, Chas. Zutz.

On November 19th 1895, I began the survey. J. A. James, Scott Hodges were selected as Chainmen and Jacob Butts as Flagman all were duly sworn, I met at the South East corner of Section 11 I found a corner stone & ran over to a flag on the South West corner of sec. 11 at 2338 ft East bank Verdigris River at 2640 ft. down stake on gravel bar near west side of the River. From the S. W. corner of Section 11 I ran East on Sec. line at 3960 ft. down stake at temporary N.E. corner. N. $10^{\circ} 15' 15''$ W. $1/4$ Sec. 14, T. 33, R. 16, E. at 2608' stake down a temporary $1/4$ post on South line Sec. 11 as this line is 32 ft. short & corrects 16 ft. East, as true corner and down stake, as a witness to this corner I made a X on the top of the S. W. corner stone (Judy corner) to the West pier of the bridge known as the W. Taggart Bridge. This X is N. $18^{\circ} 15' 15''$ E. 46 ft. distant, I also set a sand stone as witness to this corner 144.6 ft. West of true corner on Sec. line I also set a witness stone as witness to the $1/4$ corner South line Sec. 11, on the $1/4$ line 256.6 ft. N. $10^{\circ} 15' 15''$ W. from the true corner.

From the N. W. corner of Section 11, (a stone) I ran East on Sec. line at 2015 ft. witness edge Verdigris River Meander River on the line 276 ft. by actual measurement, at 2391 ft. top of bank on East side of the River, at 2640 down stake at temporary $1/4$ post on the North line of Sec. 11 at 5223 ft. corner out 12 ft. South of a stone the N.E. corner. Sec. 11. Now as the temporary $1/4$ post on the North line of Sec. 11 was witnessed by the Oak tree 30ⁱⁿ in diameter N. $83^{\circ} 15' 15''$ E. 92 links distant and an Oak tree 30ⁱⁿ in diameter S. $63^{\circ} 50' 15''$ E. 36 links distant the last mentioned tree stump I found placed my transit over it. Ran N. $63^{\circ} 50' 15''$ W. 24 ft. down stake from this stake as temporary corner & ran N. $83^{\circ} 15' 15''$ E. 62 ft. the boys dug down and found an Oak stump a very large one. This was conclusive and at the point where the stake was driven I set a lime stone $26 \times 18 \times 12$ marked $1/4$ as the $1/4$ post on the North line of Section 11. From the S.E. corner (a stone) of Section 11 I ran N. $0^{\circ} 30' 15''$ W. at 2640 ft. $1/4$ post at 5280 ft. N.E. corner Sec. 11.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. CRANE & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

_____, Kansas, _____ 189____.

M _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
County, State of Kansas.

From the $1/4$ post across on the West line of Section 11 I ran East on random line at 2400 ft. witness edge of Verdigris River measured the River 193 ft. wide at 2640 ft. down stake on East bank of River at 5237 ft. corner out 4 ft. North of the $1/4$ post correction for center would be 2 ft. South. From the $1/4$ post on North line Sec. 11 I ran S. $80^{\circ} 10' 15''$ E. with measuring the line & corner out 54 ft. West of the $1/4$ post on the South line of Sec. 11. From the $1/4$ post on South line Sec. 11 I ran true line N. $0^{\circ} 46' 15''$ W. corner out to $1/4$ post North line Sec. 11 as the $1/4$ line intended on a steep slope of the River bank & down a stake at the intersection and set a witness stone a lime stone $30 \times 18 \times 12$ marked XX 40 ft. South of true corner.

At a point on the South line of Section 11, 3948 ft. East of the South West corner of Section 11, I set a sand stone $26 \times 13 \times 2 1/2$ marked X as the N.E. corner of the $1/4$ N.E. $1/4$ Sec. 14, T. 33, R. 16, E. I measured the river and located it on the flat as shown on opposite page measurement well up of the River bank when not otherwise stated. This finished the survey on November 21st 1895.

Cor $8^{\circ} 30' 15''$ E.

L. L. Hibbard -
County Surveyor.