

This is to certify that S. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by J. W. Kenyon to survey and subdivide Section 29, Township 33, Range 16, East, 1st Meridian 1896. The following named parties were notified that a survey of the above described Section would take place on Feb. 11<sup>th</sup> 1896. Sylvester F. Scovel, J. Chandler, J. W. Kenyon, John Linniger, Fred Brier, aff. Goodlock Bonnett, Clark Milligan, aff. Thomas Clark, E. J. Meeks, aff. C. J. Collins, David Sanford, Frank Clark, Benard Hankey, Daniel Martin.

Feb. 11<sup>th</sup> 1896

L. O. Slater, John Davis, G. J. Miner.  
I began the survey on Feb. 11<sup>th</sup> 1896 and J. W. Carpenter was selected as chairman and was duly sworn. I went to the North East Corner of Section 29 and found a stone marked with 4 marks 1111, supposed to be the permanent stone from this stone I ran West at 2640 ft. North stake as temporary 1/4 post on the North line of Sec. 29. From this temporary 1/4 corner I ran West at 2610 ft. Corner out 2 1/2 ft. South of the North West corner of Section 29 which is a stone marked 1111. Connections for this 1/4 temporary 1/4 post is 13 ft. East and 10 1/2 ft. North. From the North West corner of Section 29 I ran South at 1320 ft. down stakes as temporary S.W. Cor. of the N.E. 1/4 of the N.W. 1/4. At 2640 ft. down stakes as temporary 1/4 post on the West line of Section 29 at 3960 ft. down stakes as temporary N.W. Cor. 3/4 S.W. 1/4 Sec. 29. At 5256 ft. found Part of Government Stone. From this stone ran S. 89° 45' E. at 1320 ft. down stakes at 2635 ft. stone 1/4 post bearing 90. Marks but small in size. From this stone I ran S. 89° 45' E. at 1320 ft. down stakes at 2626 ft. S.E. Cor. of Sec. 29 stone bearing Marks 1111. From this stone the S.E. corner Sec. 29 I ran North at 1320 ft. down stakes as temporary N.E. Cor. to S.E. Cor. Sec. 29. At 2640 ft. down stakes as temporary 1/4 post on East line of Sec. 29. At 3960 ft. down stakes as temporary S.E. Cor. to N.E. 1/4 Sec. 29. At 5268 ft. the N.E. corner Sec. 29 our starting point. Wednesday Feb. 12 1896. At a point 15 ft. East and 10 1/2 ft. North of the stake down as temporary 1/4 post on the North line of Sec. 29 I set a sand stone 18" x 11" x 5" marked 1/4 for the 1/4 post on the North line of Sec. 29. From this 1/4 post I ran N. 89° 45' W. at 1312 1/2 ft. set stake as true point for 1/4 cor. At a point 1314 ft. South of the North West corner Sec. 29 I set a sand stone 18" x 14" x 4" marked X as S.W. Cor. N.E. 1/4 Sec. 29. At a point 2628 ft. South of the N.W. Cor. Sec. 29 I set a flag stone 16" x 16" x 1 1/4" marked 1/4 for the 1/4 post on the West line of Section 29. At a point 1314 ft. North of the S.W. corner Sec. 29 I set a sand stone 28" x 16" x 9" marked 1/8 for N.W. corner 3/4 S.W. 1/4 Sec. 29. At the South West corner of Sec. 29 I set a sand 33" x 24" x 9" marked 1111. This stone was set at the same point as the old corner which the old corner reads this stone as witness to true point. At a point 2634 ft. S. 89° 45' E. I found this S.W. Cor. Sec. 29. I set a sand stone 28" x 12" x 7" marked 1/4 as the 1/4 post on the South line of Sec. 29. The old marked stone is beside the one and I set the old stone was marked 1/4 by four or supposed to be a four stone. At a point 1314 ft. S. 89° 45' E. from the 1/4 post on the South line of Section 29 I set a sand stone 28" x 12" x 7" marked 1/8 at S.E. Cor. S.W. 1/4 S.E. 1/4 Sec. 29. At a point 1317 ft. North of the S.E. corner Sec. 29 I set a sand stone 21" x 13" x 6" marked 1/8 as N.E. corner 3/4 S.E. 1/4 Sec. 29. At a point 2634 ft. North of S.E. Cor. Sec. 29 I set a sand stone 27" x 18" x 5" marked 1/4 for the 1/4 post on East line Sec. 29. Thursday Feb. 13<sup>th</sup> 1896. At the S.E. Cor. of the N.E. 1/4 Sec. 29 I set a sand stone 24" x 11" x 5" marked 1/8. I set a flag on this last described corner Ran N. 89° 50' W. to opposite corner on West west. I ran the 1/4 lines at the junction set a sand stone 24" x 10" x 8" marked X. I set flag on the 1/4 post Monday S.W. 1/4 of Sec. 29. At the S.W. Cor. N.E. 1/4 S.W. 1/4 Sec. 29 I set a flag stone 23" x 9" x 2 1/2" marked 1/8. This point was established by the intersection of N.E. 1/4 S.W. 1/4 Sec. 29 from true corner. At the S.W. corner N.E. 1/4 of the N.E. 1/4 Sec. 29 I set a sand stone 24" x 11" x 8" marked 1/8. At the N.W. corner S.E. 1/4 N.E. 1/4 Sec. 29 I set a sand stone 24" x 12" x 6 1/2" marked 1/8. At a point 1314 ft. South of the center section 29 on 1/4 line I set a sand stone 26" x 14" x 4" marked X as N.W. Cor. 3/4 S.E. 1/4 Sec. 29. At the N.E. Cor. S.W. 1/4 S.E. 1/4 Sec. 29 I set a sand stone 20" x 16" x 5" marked X. At the N.W. corner S.E. 1/4 N.W. 1/4 Sec. 29 I set a sand stone 24" x 18" x 3 1/2" marked 1/8. This completed the survey on Feb. 13<sup>th</sup> 1896.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.  
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

Kansas, 189.

You are hereby notified that, at o'clock A. M., on the day of 189, I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,  
County, State of Kansas.

marked 1/8 at S.E. Cor. S.W. 1/4 S.E. 1/4 Sec. 29. At a point 1317 ft. North of the S.E. corner Sec. 29 I set a sand stone 21" x 13" x 6" marked 1/8 as N.E. corner 3/4 S.E. 1/4 Sec. 29. At a point 2634 ft. North of S.E. Cor. Sec. 29 I set a sand stone 27" x 18" x 5" marked 1/4 for the 1/4 post on East line Sec. 29. Thursday Feb. 13<sup>th</sup> 1896. At the S.E. Cor. of the N.E. 1/4 Sec. 29 I set a sand stone 24" x 11" x 5" marked 1/8. I set a flag on this last described corner Ran N. 89° 50' W. to opposite corner on West west. I ran the 1/4 lines at the junction set a sand stone 24" x 10" x 8" marked X. I set flag on the 1/4 post Monday S.W. 1/4 of Sec. 29. At the S.W. Cor. N.E. 1/4 S.W. 1/4 Sec. 29 I set a flag stone 23" x 9" x 2 1/2" marked 1/8. This point was established by the intersection of N.E. 1/4 S.W. 1/4 Sec. 29 from true corner. At the S.W. corner N.E. 1/4 of the N.E. 1/4 Sec. 29 I set a sand stone 24" x 11" x 8" marked 1/8. At the N.W. corner S.E. 1/4 N.E. 1/4 Sec. 29 I set a sand stone 24" x 12" x 6 1/2" marked 1/8. At a point 1314 ft. South of the center section 29 on 1/4 line I set a sand stone 26" x 14" x 4" marked X as N.W. Cor. 3/4 S.E. 1/4 Sec. 29. At the N.E. Cor. S.W. 1/4 S.E. 1/4 Sec. 29 I set a sand stone 20" x 16" x 5" marked X. At the N.W. corner S.E. 1/4 N.W. 1/4 Sec. 29 I set a sand stone 24" x 18" x 3 1/2" marked 1/8. This completed the survey on Feb. 13<sup>th</sup> 1896.

Var. 8° 30' E.

Witness at Independence March 7<sup>th</sup> 1896

S. L. Hibbard  
County Surveyor.

Inde Independence Montgomery Co. Kansas March 27<sup>th</sup> 1897.

In the matter of the survey of Section 29, Township 33, R. 16, E. Ordered by John Kenyon & others, Wm. Williams, Huntkin and Beattie, Chandler owners of Lands in and adjoining the above described Section, Waver all notices and agree to abide by the survey as now on record.

Signed } William Huntkin.  
Beattie & Chandler.