

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. L. Hibbard County Surveyor of Montgomery Co. Kansas was ordered by M. E. Kelso to survey and subdivide Section Eleven (11) Township Thirty-four (34) Range Thirteen East, (13) On February 24th 1896 the following named parties were notified that a survey of the above described section would be made on March 3rd 1896. W. H. Halsted, R. B. Knocks, J. L. Cramer, L. H. Ford, John Callahan, J. C. Robinson, E. H. Lamb, E. D. Lamb, Leona Dunham, L. M. Prather were selected as chairman and were duly sworn. From the S.E. corner of Section 11, T. 34, R. 13, E. 1 ran North on Sect line between Sects 11 & 12, at 1030 ft. Bee Cuck at 1640 ft. Same Cuck at 2640 ft. 1/4 post from this 1/4 post on the East line Sec. 11 & ran North 8°30' W. at 1320 ft. drove stakes as temporary cor. at 2635 ft. a stone the North East Cor. Sect. 11. Correction for temp. as S.E. Cor. N.E. 1/4 N.E. 1/4 Sec. 11. would 2.3 ft. South from the North East corner Sec. 11, & ran S. 89°45' W. at 1315 ft. a stone at 2630 ft. Came out 8 ft. South of 1/4 post on North line of Sec. 11. From this 1/4 post & ran (which had witness hole standing) E. ran S. 89°55' W. at 250 ft. Cuck at 1125 ft. Bee Cuck at 2640 ft. a stone the N.W. corner Section 11 on Chautauque Co. line. From this N.W. corner Sect. 11 & ran South on County line at 2678 ft. the 1/4 post on West line Sect. 11, driving government marks. From this 1/4 post & ran South at 2648 ft. Came out 8 ft. West of the former corner which & found standing & driving gov. marks. Closed for the day, March 3rd 1896. From the government stone at the South West corner of Section 11, T. 34, R. 13, E. 1 & ran N. 89°30' E. at 1340 ft. top of bluff at 2658 ft. drove stake (found this sand stone supposed to be for Cor. 1st sec.) from this point & ran N. 89°30' E. at 1340 ft. a stone at 2678 ft. S.E. corner Sec. 11 (Came out 2 ft. South of corner.) For 1/4 post on South line Sec. 11, & set a sand stone 15"x12"x3" marked 1/4. From this 1/4 post on South line Sec. 11 & ran North on 1/4 line at 2640 ft. drove stake as temporary center Sec. 11. From temporary center Sect. 11 & ran North at 230 ft. Bluff at 1800 ft. Bee Cuck at 2500 ft. Bluff Cuck at 2668 ft. Came out 6 ft. East of the 1/4 post. At a point 1320 ft. West. on Sec. line from the 1/4 post on North line Sec. 11 & set a sand stone 22"x11"x3" marked X as N.W. corner E 1/2 N.W. 1/4 Sec. 11. From 1/4 post West line Sec. 11 & ran N. 89°30' E. at 2652 ft. Temp. 1/4 line running N+3. Closed for the day March 4th 1896. J. H. McNally sworn as chairman in place of Halby. From temporary center corner Sec. 11 & ran N. 89°30' E. at 200 ft. top of bluff at 600 ft. bottom at 2240 ft. Bee Cuck at 2661 ft. Came out 4 ft. South of 1/4 post on East line Sec. 11. At a point 1318 ft. North of 1/4 post on East line Sec. 11 & set a sand stone 18"x6"x4" marked 1/8. For S.E. Cor. N.E. 1/4 N.E. 1/4 Sec. 11. From this last corner & ran S. 89°32' W. 850 ft. Bee Cuck at 1330 ft. drove stake temporary S.W. Cor. N.E. 1/4 N.E. 1/4 Sec. 11 & then went to the N.W. Cor. N.E. 1/4 N.E. 1/4 Sec. 11, & ran South at 660 ft. set a sand stone 17"x6"x3 1/2" for S.E. Cor. N 1/2 N.W. 1/4 N.E. 1/4 Sec. 11. At 1100 ft. Bee Cuck at 1328 ft. set a sand stone 24"x6"x5" marked X as S.W. Cor. N.E. 1/4 N.E. 1/4 Sec. 11. at a point 660 ft. South on 1/4 line from the 1/4 post on the North line Sec. 11. & set a sand stone 18"x6"x3" for S.W. Cor. N 1/2 N.W. 1/4 N.E. 1/4 Sec. 11. at the center of Sect. Eleven at intersection of the Quarter lines & set a sand stone 25"x12"x6" marked X as the center of Sect. 11. at a point 1324 ft. South of the center of Sec. 11 on the 1/4 line & set a sand stone 40"x12"x8" marked X as S.E. Cor. N 1/2 S.W. 1/4 Sec. 11. at a point 1324 ft. West of the center of Sec. 11 & set a sand stone on 1/4 line 30"x6"x5" marked X, as S.W. Cor. E 1/2 N.W. 1/4 Sec. 11. at a point 1324 ft. South of the 1/4 post on West line Sec. 11 & set a sand stone on County line 24"x10"x4" marked X as S.W. Cor. N 1/2 S.W. 1/4 Sec. 11. This completed the survey. Ran 8°30' E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.....

M.....
You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

Witness at Independence Montgomery Co. Kansas March 21st 1896.

S. L. Hibbard—
Co. Surveyor.