

This is to Certify That E. L. Hubbard, County Surveyor of Montgomery County Kansas as was ordered by J. W. Moore to Survey and Subdivide Section 23, Township 34, Range 13, East. On February 24th 1896 The following named parties were notified That a Survey would begin on March 4th 1896 of the above described Section

James Heffernan, Chas. Robinson, J. W. Moore, George Blackmore, William Clark, M. H. Horner, Harriet H. Ross, E. I. Mears and Marion Kelso.

On March 4th 1896 I began the Survey, L. M. Prather and J. H. McHally were chosen as chainmen and were duly sworn. I began at the N.E. Corner of Section 23 a stone found this stone 2. ran S. 89° 30' W. at 2540 ft. Bee Creek at 3705 ft. A Birch tree blazed and marked as witness line by government field notes. The creek bank had slid into the creek, but we found to the government stone in the creek having located the point where the government stone stood I measured 40 ft. West and set a sand stone 30x6x6" marked 1/4 with government stone beside it as witness to true corner which is 40 ft. East of the stone set. I ran S. 89° 30' W. at 4335 ft. Center E. & W. R.R. at 5347 ft. Section line down stake as temporary sec. cor. I then went to the South West Corner of Section 23 a stone on the County line and ran N. 89° 30' E. at 600 ft. Bee Creek at 800 ft. Bee Creek at 1500 ft. Bee Creek at 2640 down stake as temporary 1/4 post on South line Sec. 23. at 5287 ft. found out 82 ft. North of Heffernan corner. I then went to the North East Corner Sec. 23. Ran S. 0° 15' E. at 2390 ft. Cotton Creek Bridge at 2640 down stake as temporary 1/4 post on the East line of Section 23 at 5282 ft. down stake as temporary S.E. Corner Sec. 23. I found this point as true corner I went to the 1/4 post a stone on the South line of Section 24 and ran West on sec. line at 2640 ft. down stake this stake was 2 ft. West of stake set by N+South run making this the true point for the Sec. Corner I set a sand stone 36x8x6" marked 1111 for the S.E. Corner Sec. 23 at a point midway between S.E. corner + S.W. corner of Sec. 23 I set a sand stone 18x12x6" marked 1/4 for the 1/4 post on the South line of Sec. 23. From a stone the South corner Sec. 23 I ran N. 0° 30' W. on County line at 2601 ft. found marked stone as 1/4 post at 4903 ft. Center of the E. & W. R.R. at 5200 ft. stake temporary N.W. cor. Sec. 23. Then I set a sand stone 24x8x6" marked 1111 for the N.W. corner Sec. 23. At the 1/4 post on East line Sec. 23 I set a sand stone 28x9x6" marked 1/4 from the true point for 1/4 post on the North line of Sec. 23 I ran S. 0° 30' E. at 10 ft. Bee Creek line runs in creek for 200 ft. at 673 same creek (Samm Creek) line runs along west bank for 200 ft. at 2620 down stake as temporary to center Sec. 23. at 3605 ft. Bee Creek at 5240 ft. 1/4 post on South line Sec. 23 I set for center of Sec. 23 a sand stone 10x10x3" marked XXX This completed the Survey on March 6th 1896.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

189.

M.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

Var. 8° 30' E.

Witness at Independence
Montgomery Co. April 14 1896
E. L. Hubbard,
S. Surveyor.