

Survey No. , Section 7, Town 34 South, Range 14.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, S. L. Hibbard, County Surveyor of Montgomery Co., Kansas, was ordered by George H. Halby to survey and subdivide Section Seven (7) Township 34, Range 14 East on March 7<sup>th</sup> 1896 that following named parties were notified that survey of the above described Section would be made on March 16<sup>th</sup> 1896. H. Haag, Geo. Halby, J. W. Bell, Joseph Robinson, Anna Blaker, Van Meter, J. C. Blair, David Halby, Lee Carr, Chas. Haas, J. J. Fox, Blackfilter R. (Pauls) and March 16<sup>th</sup> 1896 & began the survey. E. B. Meadeball and Milton Brunswick were selected as chairman and were duly sworn & went to the north end and dug down and found the lower part of the fore. stone. Starting from this point as the North West corner of Sec. 7. I ran S 0° 15' W. (Var. 83° E) at 1320' down stake at 2638 ft. a stone the 1/4 post on west line Sec. 7. From 1/4 post west line Sec. 7 ran S 0° 15' W. on Range line at 980 ft. Center C. K. & M. R. R. at 2640 ft. a stone S. W. corner Sec. 7. From this south S. W. corner of Sec. 7 I ran N. 89° 40' E. at 1309 1/2 ft. down stake at 2615 ft. down stake as temporary 1/4 post on south line Sec. 7. From this temporary 1/4 post on south line Sec. 7 I ran S 89° 40' E. at 2631 ft. found out 2 ft. South of stone as S. E. corner of Sec. 7. From S. E. corner Sec. 7 ran N. 0° 30' E. at 2575 ft. found Government 1/4 post a lime stone. From this 1/4 post I ran with 0° 30' E. at 330 ft. stake as N. E. corner of 20 acre tract off south side N. E. 1/4 Sec. 7. At 1375 ft. Cotton Creek 1923 Center C. K. & M. R. R. at 2638 ft. a stone N. E. corner Sec. 7. I went to the south line Sec. 7 and set a lime stone. 7 ft. West of temporary 18' x 12' x 7' marked 1/4 for 1/4 post on south line Sec. 7. March 17 1896 at a point 1290' N. 89° 40' E. from S. W. corner Sec. 7 I set a lime stone 26' x 16' x 3' as S. E. corner of 1/4 No. 4. Sec. 7. From 1/4 post south line Sec. 7 I ran N. 0° 30' E. on 1/4 line at 1310 ft. down stake as temporary N. W. corner S. 1/2 S. E. 1/4 Sec. 7. At 2608 ft. down stake as temporary center Sec. 7 in track at 3319 ft. Center C. K. & M. R. R. at 5242 ft. 1/4 post North line Sec. 7 (a stone). From 1/4 post North line Sec. 7 I ran West at 1320 ft. down stake at 2660 ft. N. W. corner Sec. 7. At the North West corner Sec. 7 I set a lime stone 36' x 12' x 8' marked 1111 and put the broken piece of the fore. stone beside it as witness to true point. At a point 1319 ft. South on Range line from N. W. corner Sec. 7 I set a lime stone 18' x 11' x 6' marked X as S. W. corner Sec. 7. From 1/4 post West line Sec. 7 I ran East on range line at 1095 ft. Center C. K. & M. R. R. at 2615 ft. down stake as N. E. corner S. 1/2 Sec. 7. At intersection of 1/4 line down stake as temporary center Sec. 7. Wednesday March 18<sup>th</sup> 1896 from center temporary corner Sec. 7 I set 5 ft. North an east of Help's Run East on Range line at 1319 ft. S. 89° 50' E. corner out 2 ft. 10' North of 1/4 post East line Sec. 7 I cornered temporary center Sec. 7. 8 ft. South and set from intersection of 1/4 line made by E. & M. Run. I set a lime stone 19' x 13' x 6' marked XX as center Sec. 7. At a point 1287 1/2 ft. N. 0° 30' E. from S. E. corner Sec. 7 I set a lime stone 32' x 6' x 8' marked X as N. E. corner S. 1/2 S. E. 1/4 Sec. 7. Beside the Government 1/4 post on East line Section 7 I set a sand stone 20' x 9' x 6' marked 1/4 as witness to true point. At a point 330 ft. N. on East line Sec. 7 I set a sand stone 18' x 6' x 8' marked X as N. E. corner of 20 acre tract. I set a lime stone at N. W. corner of 20 acre tract size 15' x 10' x 6' marked X at a point 1307 1/2 ft. North on 1/4 line from 1/4 post on south line Sec. 7 I set a lime stone 24' x 9' x 4' marked X as N. W. corner S. 1/2 S. E. 1/4 Sec. 7. At a point 1314 ft. East from 1/4 post on West line Sec. 7 I set a lime stone 22' x 6' x 3' marked X as N. E. corner S. 1/2. At a point also I set a sand stone 24' x 7' x 6' marked X as S. E. corner N. W. 1/4 N. W. 1/4 fractional Sec. 7.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.

You are hereby notified that, at o'clock A. M., on the day of 189, I will begin a survey on Section Town South, Range, in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,  
County, State of Kansas.

at a point 330 ft. North on 1/4 line from center Sec. 7 I set a lime stone at N. W. corner of 20 acre tract size 15' x 10' x 6' marked X at a point 1307 1/2 ft. North on 1/4 line from 1/4 post on south line Sec. 7 I set a lime stone 24' x 9' x 4' marked X as N. W. corner S. 1/2 S. E. 1/4 Sec. 7. At a point 1314 ft. East from 1/4 post on West line Sec. 7 I set a lime stone 22' x 6' x 3' marked X as N. E. corner S. 1/2. At a point also I set a sand stone 24' x 7' x 6' marked X as S. E. corner N. W. 1/4 N. W. 1/4 fractional Sec. 7.

This completed the survey on March 18<sup>th</sup> 1896 for S. 30' E.

Noted at Independence Montgomery Co.

April 17<sup>th</sup> 1896

S. L. Hibbard -  
County Surveyor.