

This is to certify That L. S. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by W. V. Bowersock to survey and subdivide Section 17, T. 34. R. 14. E. On March 17th 1896 That following named parties were notified that a survey of the above described section would be made on March 18th 1896 Doc Van Meter agt, Chas Hays J. C. Blair agt, Cooper Flatfilter Merriam & Co. Swings Bank Frank Cradlock E. J. Meers agt, Esiah H. Clair, Frank Hafsmann C. H. Huchman (Meers agt), Thomas Bell for Barr B. Hennigan, John Forman, James Bell, John Bowersock, Milton Bowersock, W. V. Bowersock J. C. Ross, Joseph Chandler,

On Wednesday March 18th 1896 I began The Survey Milton Bowersocks
and Ernest Mendenhall were selected as Chaimmen and were duly sworn. From a stone the
North West Corner of Section 17, Township 34th Range 14th E. I ran South 0°30'E. at 2652 ft. drove a stake as
temporary 1/4 post on west line Sec. 17. From this temporary 1/4 post I ran South 0°30'E. at 975 ft. Cotton Creek
at 1138 ft. Same creek at 1325 Same creek at 1800 ft. Same Creek at 2650 ft. drove stake as temporary
South West Cor. Sec. 17. From this last mentioned stake I ran S. 89°30'E. at 1320 ft. drove stake at 2640 ft.
drove stake as temporary 1/4 post on South line Sec. 17. From this temporary 1/4 post I ran S. 89°30'E. at 2640 ft.
drove stake as temporary S.E. Cor. Sec. 17. From this temporary S.E. Cor I ran N. 0°30'E. at 2640 ft. drove stake
as temporary 1/4 post on East line Sec. 17. finished for the day. March 19th 1896 From temporary 1/4 post
on the East line of Section 17, I ran N. 0°30'E at 2640 drove stake as temporary N.E. Cor. Sec. 17
thence North 89°15'W at 1320 ft. drove stake at 2640 ft. drove stake as temporary 1/4 post on North line Sec. 17.
From temporary 1/4 post on North line Sec. 17 I ran North 89°25'W. at 1320 drove stake at 2704 carried out 4 ft
South of N. West Cor. Sec. 17. at 1/4 post on West line Sec. 17 set a lime stone 30x14x10 marked 1/4 this stone
is 2654 ft. S. 0°30'E. of N.W. Cor. Sec. 17. At the S.W. Cor Sec. 17. set a lime stone 30x12x10 marked 1111
at a point S. 89°15'E. from South West Cor. Sec. 17 set a lime stone 26x8x4 marked 1/4 as 1/4 post

Var. $8^{\circ}30'E$

Latid at Independence April 17th 1896

S. L. Hibbard
Co. Surveyor.