

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. L. Hibbard County Surveyor of Montgomery Co. Kansas was ordered by Fred Bingham to survey and locate his lands in Sec. 33+34 Township 33, Range 16 E., and Subdivide the Section. The following named parties were notified that a survey of the above named sections would be made on April 23rd 1896. Geo. Hall, Fred Bingham, B. C. Chaney, John Clay, Joseph Jackson, New England Land & Trust Co., Mathewson & Sons, Co., German Insurance Co., Mary E. Buleland, J. W. Corbitt, Eudora Whitman, Clark Williams, Aft. J. Miller, Perry Butler, Ewing Miller, Annie H. Mury, James Burroughman, C. C. Logston, William Brier, E. S. Souford, Mable, & Monroe.

On April 23rd 1896 I began the survey and subdivisions of Sec. 33+34, T. 33, R. 16 E., as above. J. M. Loddard and T. V. Clay were chosen as chainmen, Mr. Bingham Chapman was duly sworn & went to a stone the Government's post on the Township line on South line of Section 34 T. 33, R. 16 E., & ran N. 89° 30' W. at 1320' down stake at 2640' corner out 2 ft. South of a point supposed to be the four corner of portion of the original stone remaining this point & located as the South East corner of Sec. 33. I then went to the North West corner of Sec. 33 and ran South 8° 30' W. at 2640' down stake as temporary N. E. corner Sec. 33. From this temporary S. W. corner Sec. 33, I ran S 89° 30' E. at 2640' down stake temporary 1/4 post at 5280' ft. corner out 7 ft. South of point located as S. E. corner Sec. 33. As this South line was 27 ft. short by our measurement, and as temporary S. W. corner Sec. 33 was 60 ft. East of a help running N. & S. To ascertain whether I could move this temporary location that I went to a stone the 1/4 post on the South line of Section 32 T. 33, R. 16 E. & ran S 89° 30' E. at 2640' ft. down stake which was 23 ft. West and 6 ft. North of the temporary S. W. corner of Sec. 33. I made this point the place for the true corner. From the N. W. corner Sec. 33, I ran S 89° 30' E. at 2638' 1/4 post a stone supposed to be Government's post at 5280' down stake as temporary N. E. corner Sec. 33. Friday May 24th 1896 From the Government's 1/4 post on North line Sec. 34 T. 33, R. 16 E., I ran N. 89° 30' W. at 2624' stake as temporary N. E. corner Sec. 33. Located stake 8 ft. West and set a sand stone 24x11x6" marked 1111 for corner to Sec. 27, 28, 33+34. At the South East corner Sec. 33 set a sand stone 26x8x6" marked 1111 for 1/4 post on East line Sec. 33 set a sand stone 24x15x8" marked 1/4 at the South West corner Sec. 33 set a sand stone 28x14x5" marked 1111. For 1/4 post on South line Sec. 33 set a line stone 28x16x6" marked 1/4, at a point midway between the 1/4 post on the South line of Sec. 33 and the S. E. corner Sec. 33, & set a line stone 38x14x5" marked X as the S. W. corner, E. 1/2 S. E. 1/4 Sec. 33. (I found part of the old Government stone 1/4 post on South line Sec. 33 which I placed beside the one set for true corner in the same place) As it rained & adjourned until May 1st 1896. May 1st 1896 Survey continued. The above named chainmen assisting. At a point 1320 ft. S. 89° 30' E. of the S. W. corner Sec. 34, I set a line stone 24x16x6" marked X as S. E. corner, W. 1/2 S. W. 1/4 Sec. 34, T. 33, R. 16 E.,. Located temporary stake as 1/4 post on West line Sec. 33, 11 1/2 ft. West and 3 ft. North of down found part of old Government stone & set a line stone 28x15x4" marked 1/4 with the piece of old Government stone beside it. I set flags on the 1/4 post and connected them by straight lines at their intersection & set a line stone 24x13x4" marked X X as the center corner to Sec. 33, T. 33, R. 16 E. At a point midway between the center of Sec. 33 and the 1/4 post on the East line of Sec. 33, I set a 26x12x4 1/2" marked X as N. W. corner, E. 1/2 S. E. 1/4 Sec. 33. At a point 1318 ft. East on the 1/4 line from the 1/4 post on West line Sec. 34 T. 33, R. 16 E. I set a sand stone 30x14x10" marked X as the N. E. corner, W. 1/2 S. W. 1/4 Sec. 34. At the center Sec. 34 T. 33, R. 16 E. I set a sand stone 24x11x9" marked X X as the center of Section 34 by measuring North from 1/4 post on South line Sec. 34, and East from 1/4 post on West line Sec. 34 T. 33, R. 16 E. This completed the survey.

NOTICE—Surveyor's Permanent Record, State of Kansas.

I, Geo. W. Crane & Co., Printers and Binders, Topeka, Kas. Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 189 .

M .

You are hereby notified that, at . o'clock A. M., on the . day of . 189 ., I will begin a survey on Section . Town . South, Range . in which you are interested, and shall continue the same from day to day until completed. Commencing at the . corner of said Section, I shall permanently establish .

County Surveyor, . County, State of Kansas.

For 1/4 post on East line Sec. 33 set a sand stone 24x15x8" marked 1/4 at the South West corner Sec. 33 set a sand stone 28x14x5" marked 1111. For 1/4 post on South line Sec. 33 set a line stone 28x16x6" marked 1/4, at a point midway between the 1/4 post on the South line of Sec. 33 and the S. E. corner Sec. 33, & set a line stone 38x14x5" marked X as the S. W. corner, E. 1/2 S. E. 1/4 Sec. 33. (I found part of the old Government stone 1/4 post on South line Sec. 33 which I placed beside the one set for true corner in the same place) As it rained & adjourned until May 1st 1896. May 1st 1896 Survey continued. The above named chainmen assisting. At a point 1320 ft. S. 89° 30' E. of the S. W. corner Sec. 34, I set a line stone 24x16x6" marked X as S. E. corner, W. 1/2 S. W. 1/4 Sec. 34, T. 33, R. 16 E.,. Located temporary stake as 1/4 post on West line Sec. 33, 11 1/2 ft. West and 3 ft. North of down found part of old Government stone & set a line stone 28x15x4" marked 1/4 with the piece of old Government stone beside it. I set flags on the 1/4 post and connected them by straight lines at their intersection & set a line stone 24x13x4" marked X X as the center corner to Sec. 33, T. 33, R. 16 E. At a point midway between the center of Sec. 33 and the 1/4 post on the East line of Sec. 33, I set a 26x12x4 1/2" marked X as N. W. corner, E. 1/2 S. E. 1/4 Sec. 33. At a point 1318 ft. East on the 1/4 line from the 1/4 post on West line Sec. 34 T. 33, R. 16 E. I set a sand stone 30x14x10" marked X as the N. E. corner, W. 1/2 S. W. 1/4 Sec. 34. At the center Sec. 34 T. 33, R. 16 E. I set a sand stone 24x11x9" marked X X as the center of Section 34 by measuring North from 1/4 post on South line Sec. 34, and East from 1/4 post on West line Sec. 34 T. 33, R. 16 E. This completed the survey.

Cor. 8° 30' E.

Dated at Independence Montgomery Co. Kansas
May 16th 1896
S. L. Hibbard
Co. Surveyor.