

This is to certify That S. L. Hubbard County Surveyor & Surveyor of Montgomery Co. Kansas was ordered by M. H. Hufferdangle to survey and subdivide Section 35 Township 34 R. 13 E. On April 27 1896. The following named parties were notified That a Survey of the above named Section would be made on May 6 1896. J. C. Ross, J. C. National Bank of Independence Kansas, May E. & Clay Adls. May J. & H. Wessner, William Robinson J. E. Storer N. W. Osborn Ed. Cockran, W. H. Hekkersoon William Pettaborn W. S. Brown J. S. Coleman I. Ellis.

On May 6 1896 I began the Survey J. C. Turk & Robert Hooks were selected as Chain Carriers, and W. C. Abel Hagerman and Mrs. J. C. Brown I went to the 1/4 post a Government Store on the West line of Section 26 T. 34 R. 13 E. and ran South on the County line at 2640 ft. down stakes & found a stone 8 ft. East and 7 ft. South of this 1/4 post by a Survey as the North West Corner of Sec. 35 T. 34 R. 13. From this stone I ran South 13' West at 1320 ft. down stakes as temporary S. E. Cor. N. W. 1/4 N. W. 1/4 Sec. 35 at 2320 ft. North Bank Little Cane River at 2663 ft. came out 9 ft. West of 1/4 post on the West line Sec. 35 T. 34 R. 13 Thence South from this last named 1/4 post at 2649 ft. Government Corner the South West Corner Sec. 35 (a sand stone) from the South West Corner Sec. 35 T. 34 R. 13 S 89° 25' E. at 1000 ft. Little Cane River at 2635 ft. the 1/4 post on South line Sec. 35 (near end of stone wall). From this Government 1/4 post and South line Sec. 35 I ran S 89° 25' E. at 2640 ft. down stakes as temporary S. E. Corner Sec. 35. From a stone South of this cor. I ran North on West line Sec. 1 T. 35 R. 13 which was 1630 ft. to the temporary S. E. Cor. to Sec. 35. Closed work for the day. May 7 1896 From the South East Corner Sec. 35 (temporary) I ran North 8° 10' 20" at 2646 ft. down stakes as temporary 1/4 post on East line Sec. 35 at 5280 ft. down stakes as temporary N. E. Corner Sec. 35. I then went to the North East Corner Sec. 26 T. 34 R. 13 S. 0° 10' E. at 5367 ft. temporary N. E. Cor. Sec. 35. Connected this corner 6 1/2 ft. South and located this point as true corner from the true corner (N. E. Cor. Sec. 35) I ran N. 89° 35' W. at 2640 ft. down stake as temporary 1/4 post on North line Sec. 35. From this temporary 1/4 post I ran N. 89° 35' W. at 4550

NOTICE—Surveyor's Permanent Record, State of Kansas.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

for the cor. as connected at a point N. 8 1/2° W. 1/2 ft. West on Sec. line from the 1/4 post on the North line Sec. 35. I set a sand stone 30x8x8" Marked X as N. W. Cor. E. 1/2 N. W. 1/4 Sec. 35. From the 1/4 post on the North line Sec. 35 I ran South on temporary 1/4 line at 2651 ft. down stakes as temporary center Sec. 35 at 5302 ft. came out 33 ft. West of 1/4 post on South line Sec. 35. Connection would be 16 1/2 ft. East for the line as center Sec. 35. From this 1/4 post on the West line Sec. 35 T. 34 R. 13 E. I ran S 89° 20' E. at 300 ft. Little Cane River at 400 ft. Valley Edge at 1316 ft. down stakes as temporary S. E. Cor. N. 1/2 N. W. 1/4 Sec. 35 and finished for the day. May 8 1896 From the temporary S. E. Cor. N. 1/2 N. W. 1/4 Sec. 35 I ran East on temporary 1/4 line (S 89° 20' E.) at 1316 ft. stake temporary East Sec. 35 which connects. From this center Sec. 35 I ran East at 2632 ft. came out 13 ft. North of 1/4 post on East line Sec. 35. Connected center 7 1/2 ft. South and set a sand stone 32x12x8" Marked X X. At a point midway between the center Sec. 35 and the 1/4 post on the West line Sec. 35 I set a sand stone 24x11x6 Marked X as S. W. Corner E. 1/2 N. W. 1/4 Sec. 35. At a point 1331 ft. South of N. W. Corner Sec. 35 on Chetangua Co. line I set a sand stone 30x9x6" Marked X as the S. W. Corner N. W. 1/4 N. W. 1/4 Sec. 35. At the S. E. Corner of the N. W. 1/4 N. W. 1/4 Sec. 35 T. 34 R. 13 E. I set a sand stone 28x10x6" X X. This completes the Survey.

For S 30' E.

Walter W. Independence Montgomery Co.,
May 30 1896
S. L. Hubbard
County Surveyor.