

This is to certify that S. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by A. B. Carpenter to survey and subdivide Section Thirty two (32) Township 31, Range 15, East. October 31st 1896 the following named parties were notified that a survey of the above described Section would be made on November 10th 1896. S. A. Smith, J. L. Chandler, E. T. Means, A. J. Caldwell, L. L. Lathin, H. Hartig, A. B. Carpenter, S. T. Burnsey, Clara E. Richardson, Midge H. Whaples, Chas. S. Ward, S. W. Brown, A. Schulthis, A. J. H. Skinner, Josina Perkins, R. A. Beck, Sarah, F. Rice.

On November 10th 1896 I began the survey William Van Hensen, + Eli Babb. were selected as chainmen Frank Bird as flagman who were duly sworn. I then went to the South East corner of Section 32 T. 31, R. 15 E. I found the Government stone standing. From this Government corner I ran North at 1320 ft. I drove W. stakes as a temporary N.E. corner to S.E. 1/4 S.E. 1/4 Sec. 32 (on side hill) at 1440 ft. top of bluff. at 2640 drove stakes as temporary 1/4 post on East line Sec. 32 at 5288 ft. Came out 8 ft. East of a point called the sec. corner & examined this stone and was satisfied that it was a portion of the gov. stone. I set a lime stone 24x26x4" marked 1111 with this small portion of Government stone beside it. for corner to Sections 28, 29, 32 + 33. I corrected temporary 1/4 post 4 ft. North and 4 ft. West here I set a lime stone beside a mark made on solid rock as the true point for the 1/4 post on the East line of Section 32. at a point 1322 ft. North of this 1/4 post I set a lime stone on the Section line 30x18x7" marked X for the N.E. corner of the S 1/2 of the N.E. 1/4 of Sec. 32. at a point 1322 ft. North on Sec. line from the South East corner of Section 32 which was 2 ft. North and 2 ft. West of the temporary corner I set a lime stone 36x22x12" marked X as the true N.E. corner of the S.E. 1/4 of the S.E. 1/4 Sec. 32. From the 1/4 post on the East line of Sec. 32 I ran random line West on the 1/4 line at 550 ft. top of bluff at 500 ft. later corner at 1310 top of bluff at 1320 set temporary corner, at 2532 top of bluff at 2640 drove stakes on side hill as temporary center Sec. 32. From this stake I ran West at 840 ft. top of bluff. + quit for the night - Nov 11th 1896 I ran due West from top of bluff a pile stone marked the night before. at 2684 1/2 ft. Came out 7 1/2 ft. North of the gov. 1/4 post which I found standing on the West line of Section 32. corrected center 3 1/2 ft. South. I then ran back from the 1/4 post on South line which was standing at 2500 ft. top of bluff at 2646 ft. true 1/4 line running E + W. as directed from stake temporary center on true E + W. 1/4 line. I ran North on temporary 1/4 line at 720 ft. top of bluff at 2640 drove stakes as temporary N.W. corner of Sec. 32. to from this corner I went West to the N.W. corner of Section 32 a Government stone standing + marked I ran S. 89° 45' E. at 2640 ft. drove stake which was 11 ft. West of the stake driven from N + S. I ran from this stake I ran S. 89° 45' E. at 2655 ft. Came out 2 ft. South of N.E. corner Sec. 32 I corrected temporary 1/4 post on North line made by E + W. run 7 1/2 ft. East + 1 ft. North here I set a lime stone 32x18x8" marked 1/4 for 1/4 post on North line Sec. 32. At the intersection of the 1/4 lines I set a lime stone 28x18x5" marked X X. at the center of Section 32. at a point midway between the center of Section 32 and the 1/4 post on the North line Sec. 32 I set a lime stone on the 1/4 line 24x18x5" marked X for the

NOTICE—Surveyor's Permanent Record, State of Kansas.
 [Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]
 _____, Kansas, _____ 189____
 M _____
 You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____
 _____ County Surveyor,
 _____ County, State of Kansas.

N.W. corner of the S 1/2 of the N.E. 1/4 Sec. 32. At the intersection of the 1/4 lines at the center Section 32 was 14 ft. West 2 ft. S. of the stake driven as temporary center corner. I corrected the temporary N.W. cor. N.E. 1/4 S.E. 1/4 Sec. 32. 7 ft. West and made a cross on a solid lime stone eight inches long and a pile of stone as true point for N.W. cor. N.E. 1/4 S.E. 1/4 Sec. 32. from this point I could see a flag at the South West corner S.E. 1/4 S.E. 1/4 Sec. 32 a stone standing I measured the distance and found it to be 2636 ft. I divided the distance at a point midway between these two corners I set a lime stone 38x20x9" marked X as the N.W. corner S.E. 1/4 S.E. 1/4 Sec. 32 T. 31, R. 15 East.

This completed the survey on Nov. 12th 1896
 Var. 8°30' E.
 S. L. Hibbard -
 County Surveyor.

Attest at Independence Montgomery County, Kansas
 Dec. 1896.
 S. L. Hibbard -
 County Surveyor.