

Survey No. _____, Section 33, Town 32 South, Range 17.

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that S. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by Leo Allison to survey and subdivide the East 1/2 of Section 33, Township 32, Range 17, E. November 22nd 1897 the following named parties were notified that a survey of the above described Section would be made on December 2nd 1897. B. F. Wood, S. M. Elmore agt for W. Pennington, W. H. Blatchford, Elizabeth L. Lewis, John Pickler, R. F. Richard agt for S.W. 1/4 of Sec. 33. On Dec. 2nd 1897 I began the survey John Wood and H. S. Stangls were selected as chainmen and were duly sworn. I found a stone at the North East corner of Section 33 I ran South 10° 10' W. at 2700' chord stakes as temporary corners. Then on dug up the found for the first corner but found no corner at 3040 ft. Small angle at 3760' Big Hill Creek at 4060' Small angle at 4460' Small angle at 5170 ft. Small angle at 5433 ft. Came out 13 ft East of station which I found standing. From this S.E. corner of Sec. 33 on Township line I ran due west at 600 ft. Big Hill Creek at 2760 ft. Came out 15 1/2 ft. North of the Government 1/4 post true bearing would be S. 89° 50' W. From this 1/4 post I ran North 1° 30' East at 1000 ft. above at 2775 ft. above stakes as temporary center to sec. 33. December 3rd 1897 from temporary center to sec. 33, I ran North 1° 30' East at 1370 a stone at 2735 ft. a stone 1/4 post on North line Sec. 33. From this 1/4 post I ran S. 89° 10' E. at 2774 ft. the N.E. corner of Sec. 33. I found a stone at 1358 ft. S. 1° 20' W. on Sec. line from North East corner of Section 33. At a point midway between the Section corners on the East line of Section 33 I set a line stone 24x18x4" marked 1/4 for the 1/4 post at a point midway between the 1/4 post on the East line of Section 33 and the South East corner I set a line stone 28x8x6" marked X as the South East corner of the N.E. 1/4 of the South East 1/4 of section 33. At a point midway midway between the center of Section 33 and the Quarter (1/4) post on the South line of Sec. 33. I set a line stone 24x10x5" marked X as the South West corner of the North half of the S.E. Quarter Sec. 33. The center of Section 33 was established by putting flags on the 1/4 posts and connecting them by straight lines at their intersections I set a line stone 40x8x8" marked X, X, as the center of section 33 I found the lines of the Section very irregular but the 1/4 posts & Sept on East line had been standing for a long time as shown by the flags. I adjourned on the evening of Dec. 3rd 1897 to the 9th day of Dec. On the 9th day of December 1897. I ran a line from the South East corner of the North half of the South East Quarter of Section No. 33 to the North West corner of the North half of the South East Quarter of Sec. 33. T. 32 R. 17, E. This completed the survey on Dec. 9th 1897. Made at Dodge City Kansas Montgomery C. Hibbard Jan 25 - 1898. Co. Surveyor

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.
[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.....

M.....

You are hereby notified that, at..... o'clock A. M., on the..... day of....., 189....., I will begin a survey on Section..... Town..... South, Range..... in which you are interested, and shall continue the same from day to day until completed. Commencing at the..... corner of said Section, I shall permanently establish.....

..... County Surveyor,
..... County, State of Kansas.