

This to certify that S. L. Hubbard County Surveyor of Montgomery Co. Kansas was ordered by John Kreinhagen to survey and subdivide Section Eleven (11) Township 32. Range 15. East. On April 8th 1898 the following named parties were notified that a survey of the above described Section would be made beginning on April 18th 1898. Sarah Newberry, William Hunter, Francis L. Graham, John Kreinhagen, Henry Rutter, C. P. Bumble, Nathan Scott, W. C. Bayles, W. H. Brook, Mrs. B. M. Armstrong, Daniel Ringo, Geo. L. Poather, William Cleverger, J. W. Bonner, Dr. Kimpton appeared at the survey. On April 18th 1898 I began the survey. I found all the corners of the section down. Lloyd Hickert and S. L. Hubbard were selected as chainmen and duly sworn from the 1/4 post where I found a portion of the original corner (4 post) on the West line of Section Eleven 7.32. R. 15. E. I ran South at 2640 ft. drove stake as temporary South West corner Sec. 11. I then went west 1/2 mile found stone 1/4 post down of Sec. 10 7.32 R. 15. E. also S. W. Cor of Section 10 is found. I then went 1/2 mile South to 1/4 post between Sections 10 & 11 and Range as above, here I found a sand stone bearing Government Marker from this stone I offset East 10 ft. (as the stone was in a hedge) and ran North at 2640 ft. drove stake corner out 2 ft. South of temporary S. W. corner Sec. 11 after going west 10 ft. to Sec. line divided distance between stakes as true point for S. W. corner Sec. 11. From this now located point as S. W. corner Sec. 11, I ran East at 1320 ft. drove stake as temporary S. E. corner S. W. 1/4 S. E. 1/4 Sec. 11. From this stake I ran East at 660 ft. drove stake as temporary S. W. corner of Kreinhagen tract at 1320 ft. drove stake in end of hedge as temporary 1/4 post on South line of Sec. 11 at 660 ft. East of last mentioned corner (1/4 post) drove stake as S. E. corner of Kreinhagen tract at 1600 ft. through 175 ft. across at 1400 ft. offset, 495 ft. South on arch of Slough ran East 300 ft. North 95 ft. from this last stake I ran East 940 ft. to Section line thence North 400 ft. to Sec. corner drove stake as temporary S. E. corner Section 11 7.32 R. 15. E. I found a witness tree as given by Government Field Notes S. 10° 45' W. from this I located the Section corner which was 2 feet East of the corner by measurement. This point I established as the true corner to Sections 11, 12, 13 & 14. Tuesday April 19th 1898. From the stake driven as S. E. corner Sec. 11 7.32 R. 15. E. I ran North on Random line between Sections 11 & 12, at 80 rods North I measured West to Slough which was 575 ft. at 2000 Elk River near water edge measured River 103 ft. = 2103 ft. at 2185 ft. W. bank at 2640 ft. drove stake as temporary 1/4 post on the East line of Sec. 11 North from this temporary 1/4 post at 180 ft. South bank of creek at 325 ft. drove stake at 600 ft. offset 250 ft. West on arch of timber thence North at 2640 ft. to Sec. line. Measured back East to Sec. line 250 ft. here the corner was found & located the corner by witness trees as given by Government Field Notes an Oak tree N. 55° 30' E. 56 ft. distant a Walnut stump S. 45° 15' E. 27 ft. distant at junction of Slough which was laying beside the Road at the Stone marker West and within 10 ft. of a Hickory tree. From this located corner I ran West on North line Sec. 11 at 1689 1/2 ft. corner V & 2 Rail Road at 2300 ft. Edge of bank cut bottom at 2645 ft. 1/4 post driving permanent marker from this 1/4 post I ran West on North line Sec. 11 at 110 ft. by corner creek at 200 ft. offset North 100 ft. on arch of bridge & ran West at 1050 ft. drove at 1400 ft. drove at 1550 ft. drove at 2640 ft. offset South to Sec. line drove stake as temporary N. W. corner Section 11 7.32 R. 15. E. - Wednesday April 20th 1898. From the 1/4 post on the West line Sec. 11 7.32 R. 15. E. I ran North on Section line between Sections 10 & 11 at 835 ft. drove stake on South bank of Elk River Measured River 113 ft. + 40 ft. W. bank at 1678 ft. drove (line runs in the draw) at 1960 ft. North bank of draw at 2632 ft. corner out 1 1/2 ft. East of temporary stake driven as N. W. corner Sec. 11. To prove this to be the true point for corner to sections 2, 3, 10 & 11 I went with 1/4 post a stone on the West line Section 2 7.32 R. 15. E. and ran South (I put a flag on N. W. corner Sec. 2. a stone standing) at 2643 ft. temporary N. W. corner Sec. 11 I erected 1 1/2 ft. North and set a sand stone 26x17x7 for corner to Sections 2, 3, 10 & 11. Marked with III. At the South West corner Sec. 11 I set a line stone 24x10x5" marked X as S. E. corner S. W. 1/4 S. E. 1/4 Sec. 11 at a point 660 ft. East of this last mentioned stone I set a line stone 24x8x6" marked X as S. E. corner of Kreinhagen tract at a point 1320 1/2 ft. set a sand stone 16x10x6" marked 1/4 at a point 1320 ft. East and on Sec. line of S. W. corner of Kreinhagen tract I set a line stone 26x9x6" marked X as S. E. corner of Kreinhagen tract. Thursday April 21st 1898. At S. E. corner of Sec. 11 7.32 R. 15. E. I set a sand stone 28x8x6" marked with III. (also set the all permanent stone which was found beside fence by Road side) by it. For 1/4 post on East line Sec. 11, set sand stone 16x9x3" marked 1/4 for 1/4 post on East line Sec. 11 7.32 R. 15. E. From 1/4 post on East line Sec. 11 I ran West at 200 ft. drove at 250 ft. cross draw at 950 ft. Drove 100 ft. wide at 2055 ft. corner V & 2 R. R. at 2540 ft. water edge of Elk River corner is in the River near West bank. From 1/4 post on North line Sec. 11 7.32 R. 15. E. I ran South on 1/4 line at 250 ft. South bank of Slough at 1300 ft. Elk River line runs in River cut a little off of West bank of River to corner. From S. W. corner Kreinhagen tract I ran North at 257 ft. East line Right of Way at 358 ft. corner V & 2 R. R. at 460 ft. West line Right of Way at 990 ft. set a sand stone 17x8x4" for N. W. corner Kreinhagen tract. From this stone I ran East parallel with the South line of Sec. 11. at 359 1/2 ft. corner V & 2 R. R. at 1320 ft. set a line stone 21x7x4" marked X as N. E. corner of Kreinhagen tract 60 acre tract. This completed the survey. For S. 10° E. Watch at Independence Mo. to Kansas. May 16 1898 S. L. Hubbard Co. Surveyor

NOTICE—Surveyor's Permanent Record, State of Kansas. } Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.
(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

Kansas, 189.....

M.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,
County, State of Kansas.

was found & located the corner by witness trees as given by Government Field Notes an Oak tree N. 55° 30' E. 56 ft. distant a Walnut stump S. 45° 15' E. 27 ft. distant at junction of Slough which was laying beside the Road at the Stone marker West and within 10 ft. of a Hickory tree. From this located corner I ran West on North line Sec. 11 at 1689 1/2 ft. corner V & 2 Rail Road at 2300 ft. Edge of bank cut bottom at 2645 ft. 1/4 post driving permanent marker from this 1/4 post I ran West on North line Sec. 11 at 110 ft. by corner creek at 200 ft. offset North 100 ft. on arch of bridge & ran West at 1050 ft. drove at 1400 ft. drove at 1550 ft. drove at 2640 ft. offset South to Sec. line drove stake as temporary N. W. corner Section 11 7.32 R. 15. E. - Wednesday April 20th 1898. From the 1/4 post on the West line Sec. 11 7.32 R. 15. E. I ran North on Section line between Sections 10 & 11 at 835 ft. drove stake on South bank of Elk River Measured River 113 ft. + 40 ft. W. bank at 1678 ft. drove (line runs in the draw) at 1960 ft. North bank of draw at 2632 ft. corner out 1 1/2 ft. East of temporary stake driven as N. W. corner Sec. 11. To prove this to be the true point for corner to sections 2, 3, 10 & 11 I went with 1/4 post a stone on the West line Section 2 7.32 R. 15. E. and ran South (I put a flag on N. W. corner Sec. 2. a stone standing) at 2643 ft. temporary N. W. corner Sec. 11 I erected 1 1/2 ft. North and set a sand stone 26x17x7 for corner to Sections 2, 3, 10 & 11. Marked with III. At the South West corner Sec. 11 I set a line stone 24x10x5" marked X as S. E. corner S. W. 1/4 S. E. 1/4 Sec. 11 at a point 660 ft. East of this last mentioned stone I set a line stone 24x8x6" marked X as S. E. corner of Kreinhagen tract at a point 1320 1/2 ft. set a sand stone 16x10x6" marked 1/4 at a point 1320 ft. East and on Sec. line of S. W. corner of Kreinhagen tract I set a line stone 26x9x6" marked X as S. E. corner of Kreinhagen tract. Thursday April 21st 1898. At S. E. corner of Sec. 11 7.32 R. 15. E. I set a sand stone 28x8x6" marked with III. (also set the all permanent stone which was found beside fence by Road side) by it. For 1/4 post on East line Sec. 11, set sand stone 16x9x3" marked 1/4 for 1/4 post on East line Sec. 11 7.32 R. 15. E. From 1/4 post on East line Sec. 11 I ran West at 200 ft. drove at 250 ft. cross draw at 950 ft. Drove 100 ft. wide at 2055 ft. corner V & 2 R. R. at 2540 ft. water edge of Elk River corner is in the River near West bank. From 1/4 post on North line Sec. 11 7.32 R. 15. E. I ran South on 1/4 line at 250 ft. South bank of Slough at 1300 ft. Elk River line runs in River cut a little off of West bank of River to corner. From S. W. corner Kreinhagen tract I ran North at 257 ft. East line Right of Way at 358 ft. corner V & 2 R. R. at 460 ft. West line Right of Way at 990 ft. set a sand stone 17x8x4" for N. W. corner Kreinhagen tract. From this stone I ran East parallel with the South line of Sec. 11. at 359 1/2 ft. corner V & 2 R. R. at 1320 ft. set a line stone 21x7x4" marked X as N. E. corner of Kreinhagen tract 60 acre tract. This completed the survey. For S. 10° E. Watch at Independence Mo. to Kansas. May 16 1898 S. L. Hubbard Co. Surveyor