

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that J. L. Hibbard County Surveyor of Montgomery Co. Kansas was ordered by Billie Helt Co. Survey and subdivide Section No. 21 Township 31 R. 16. E. On May 2 1898 the following named parties were notified that a survey of the above described Section would begin on May 12 1898 Billie Helt Patrick Mansfield George Lippy John Wallick Charles Hurl Jack Allison George Evans J. B. Brown Daniel Sharkey H. J. Schaub.

On May 12 1898 I began the survey L. M. Hichert & J. L. Hibbard chained Hichert was duly sworn duly known as chairman. I went to the N. West corner of Section 21 and found the corner gone but 3 witness trees standing and the stump of another located the corner by the Government field notes and set a sand stone 24x8x6 marked IIII for corner to sections 16, 17, 20 & 21. From this corner I ran S. 30° E. at 2640' drove stake as temporary 1/4 post on West line sec 21 at 3960' drove stake as temporary S.W. cor. S.W. 1/4 at 5253 ft stone S.W. cor. Sec 21 at a point 2646 ft south 30° E. of N.W. cor. Sec 21 set a sand stone 17x10x8 marked 4 at a point 1323 ft south on Section line from this 1/4 post I set a sand stone as South West cor. N.W. S.W. 1/4 sec 21. measured from a stone the S.W. corner of Sec. 21 East on Sec. line at 2630 ft. the Government 1/4 post standing & marked. from this stone I ran East at 2650 ft drove stake as temporary S.E. cor. Sec 21 from this temporary South East corner I ran North 30° W. at 2640' drove stake as temporary 1/4 post on East line of Sec. 21 at 5280' drove stake as temporary N.E. cor. of Sec 21 this was about 10 ft North of the center of the cross roads where old hedges were standing to ascertain whether this was too far north I went a 1/2 mile north to the 1/4 line and measured South and found the difference to be 12 ft. divided the distance leaving each section 6 ft. short on each line here I set a sand stone 18x14x5 marked IIII for N.E. cor. to Sec. 21. I ran West from this stone at 2647 ft. Government 1/4 post (which proves the N.E. cor. of Sec 21. was not set to far North) from this 1/4 post I ran west from this 1/4 post at 1320 ft drove stake as temporary N.W. cor. N.E. 1/4 S.W. 1/4 at 2640 ft corner out 2 ft North of N.W. corner to sec. 21 I corrected the stake 1320 ft East of here 1 ft. south and set a sand stone 13x11x5 marked X as N.W. cor. N.E. 1/4 S.W. 1/4 Sec 21. connected stake as temporary 1/4 post on East line sec. 21. 3 ft. south and set a sand stone 14x11x3 1/2 marked 4 at S.E. cor. Sec 21 set a line stone 18x12x6 marked IIII for corner to sections 21, 22, 27 & 28 off set on 1/4 post 10 ft. put flags ran straight lines connected for center, and set a sand stone 12x12x5 1/2 marked X as center cor. of sec. 21. measured distance from 1/4 post on North line to center Sec 21 at a point midway between these posts I set a sand stone 15x12x5 1/2 M. X as N.E. cor. S.E. 1/4 N.W. 1/4 Sec 21 at a point midway between the center of the section and the 1/4 post on the South line I set a sand stone 18x16x5 marked X as N.E. cor. S.E. 1/4 S.W. 1/4 at a point midway between the center of Sec. 21 & the 1/4 post on the West line of the Section I set a line stone 15x9x8 marked X as N.E. cor. N.W. 1/4 S.W. 1/4 Sec. 21. Set flags on 1/4 cor. to S.W. 1/4 and established the center of the 1/4 by running straight lines at the intersection I set a sand stone 18x8x7 marked X as center of S.W. 1/4 Sec. 21. At a point midway between the N.E. cor. of N.W. 1/4 S.W. 1/4 and the N.E. cor. N.W. 1/4 Sec 21 I set a sand stone 18x11x5 marked X as N.W. cor. S.E. 1/4 N.W. 1/4 Sec 21. This completed the Survey on May 18 1898. Var. 8° 10' E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189.....

M.....
You are hereby notified that, at..... o'clock A. M., on the..... day of....., 189....., I will begin a survey on Section..... Town..... South, Range..... in which you are interested, and shall continue the same from day to day until completed. Commencing at the..... corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

by running straight lines at the intersection I set a sand stone 18x8x7 marked X as center of S.W. 1/4 Sec. 21. At a point midway between the N.E. cor. of N.W. 1/4 S.W. 1/4 and the N.E. cor. N.W. 1/4 Sec 21 I set a sand stone 18x11x5 marked X as N.W. cor. S.E. 1/4 N.W. 1/4 Sec 21. This completed the Survey on May 18 1898. Var. 8° 10' E.

J. L. Hibbard.

Co Surveyor.