

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I L. L. Hibbard County Surveyor of Montgomery County was ordered by A. C. Bonstedt to Survey and subdivide Section No. 33 Township 33 Range Fourteen (14) East on April 2nd 1898 the following named parties were notified that a survey of the above described section would be made on April 18th 1898 and continue from day to day until the survey was completed, Mary E. Brainard, Peter Deffenbaugh, A. D. Berry, E. E. Taylor, L. P. Tamm, R. G. Griffin, Joseph Hall, Thomas H. Jones, James D. Devier, William H. Haynes, H. C. Martin, A. C. Bonstedt, James H. Haynes, H. C. Martin, A. C. Bonstedt, James H. Scott, Frank Hornes, E. T. Meers (agt.) J. H. Denny.

On April 18th 1898 I began the Survey H. L. Smith and David Stonypher were selected as chainmen and were duly sworn. From the North West corner of Section 33 (a stone) I ran S 0° 45' E. at 1320 ft. Stone at 2640 ft. drove stake as temporary 4 post on West line of Sec. 33 at 3960' drove stake as temporary N. W. Cor. S. W. 4 Sec 33. at 5280 ft. drove stake as temporary S. W. corner Sec. 33 I then went west and found the government stone 4 post on the South line of Sec. 32 T. 33 R. 14 E. From this 4 post I ran due East at 2645 ft. West line of Sec. 33 but Eight (8) ft. South of temporary corner made by the North and South runs corrected stake 8 ft. South as true corner I ran due East at 1320 ft. drove stake as temporary S. E. corner S. W. 4 Sec 33. at 2641' drove stake as temporary 4 post on South line Sec. 33. From this temporary 4 post I ran East on Township line at 1040 ft. drove stake at 2650 ft. drove stake as temporary S. E. corner Sec 33 From this temporary S. E. cor. I ran North 0° 25' N. at 2170' foot of hill at 2634 ft. come out 5 ft. E of Gov. 4 post which I found standing at the end of a stone fence from this stone I ran North 0° 25' N. at 2641 ft. come out 5 ft. East of N. E. corner of Sec 33. a stone which I found standing. From this stone the North East corner of Section 33 I ran West on North line of Section 33 at 880 ft. Drove at 1320 ft. drove stake as temporary N. W. corner to S. W. 4 Sec 33. at 2642 ft. drove stake as temporary 4 post on North line of sec 33. From this temporary 4 corner I ran west at 2656 ft. N. W. corner sec. 33 found the North line of sec. 33 to be 18 ft. long I connected temporary S. E. cor of Sec. 33 2 1/2 ft. west and set a line stone 16 1/2 x 11 7/8 marked IIII for S. E. Cor. to sec. 33. At a point 2674 ft. west on Township line from S. E. corner of Sec 33 I set a sand stone 24" x 8" x 4" marked for 4 post on South line of Sec 33 T. 33 R. 14 E. at a point on South line of Sec. 33 1322 ft. East of South West corner I set a sand stone 22" x 16" x 4" marked 18 for S. E. corner S. W. 4 Sec 33 T. 33 R. 14. At the South West corner Sec 33 set a sand stone 32" x 12" x 5" marked IIII at a point 1322 ft north on Sec. line from S. W. corner Sec. 33 set a sand stone 24" x 12" x 9" marked X for N. W. cor. S. W. 4 Sec 33 at a point 2644 ft North of S. W. cor. Sec 33 set a sand stone 20" x 16" x 10" marked 4 for 4 post on West line Sec. 33. At a point midway between the N. E. and N. W. corners of Section 33 I set a sand stone 24" x 8" x 4" marked 4 for 4 post on North line section 33 at a point 1324 1/2 ft. West on Section line from North East corner of sec 33 I set a sand stone 20" x 8" x 5" marked X for

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.
[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 189.....

M.....
You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

..... County Surveyor,
..... County, State of Kansas.

N. W. cor S. E. 4 Sec. 33 T. 33 R. 14 E. I put flags on 4 posts and connected them by straight lines at the intersection of these lines set a sand stone 28" x 15" x 6" marked XX as the center sec. 33 the distance from center section North to 4 post which was 2642 ft. at a point 1321 ft. North of center sec 33 I set a sand stone 20" x 4 1/2" x 3 1/2" marked X as S. E. corner N. E. 4 Sec 33 at a point 1318 1/2 ft. South of center sec 33 I set a sand stone 30" x 9" x 6 1/2" as N. E. corner S. E. 4 Sec 33 as the center of the S. W. 4 of Sec. 33 I set a sand stone 32" x 6" x 5" marked X. Stone at the S. W. corner N. E. 4 Sec 33 was broken I set a sand stone 32" x 6" x 5" marked X which completed the survey. An oak stake was driven at the S. W. corner S. E. 4 Sec. 33.
Dated at Independence Kansas April 23 1898. Var. 8° 10' E.

L. L. Hibbard.