

This is to certify that J. L. Hibbard County Surveyor of Montgomery County, Kansas was ordered by L. C. Frederick to survey his lands in Sections 5 & 8 in Township 35 Range 14 East. on February 14th 1899. The following named parties were notified that a survey of the above named Sections would be made beginning on February 22nd 1899. E. D. Cobb, J. C. Stow, G. Lilleland, Harry Broome, L. C. Frederick, S. D. Keller, J. D. Carrinder, J. T. Tammeyell, Ida May Barnes, S. H. Jack, Abraham F. Savage, Nora Clayton, A. W. Edwards, Helen C. Kerr, Stephen Sanders, Nora E. Foster, Alfred Rivers, E. L. Atwood, A. H. Skulshis, P. S. Leadman, Annie Ford, Mary Gladfelter.

On February 22, 1899 I began the survey. S. F. Keller and A. Cobb were chosen as chainmen. L. C. Frederick flagman which were duly sworn. From a marked stone setting on top of the ground bearing Government marks. I ran S 1° E. at 80 rods drove stake at 2640 ft. drove stake as temporary 4 post on East line of Section 8. T. 35, R. 14 E. From this temporary 4 post I ran S 1° E. at 1320 ft. drove stake at 2640 ft. drove stake as temporary S. East Cor. Sec. 8 which was about 30 ft. South of a stone on top of ground bearing Government marks as original corner stone. From stake as temporary S. E. Cor. of Sec. 8. I ran South between Sects 16 & 17 at 2640 ft. I was 50 ft. South of the 4 post which I found in a pile of stone, the original corner. Correction would be for S. E. Cor. Sec. 8, 33 1/3 ft. north I made this correction which came to where the original Government stone was lying. I reset the original Gov. stone and closed for the day.

Feb. 23, 1899. Survey of Sects 5 & 8 continued Keller & main chainman. From the North East corner of Sec. 8. T. 35 R. 14 E. I ran met. at 1320 ft. drove stake at 2640 drove stake as temporary 4 post at 5280 ft. drove stake as temporary N. W. Corner of Sec. 8. From a stone in center of Coffeyville & Carey wagon Road at the N. W. Corner S. 2 1/4 of Section 8. T. 35, R. 14 E. I measured north on the West line of Sec. 8 at 1320 ft. I looked & dug for the 1/4 post which is said to be buried 4 ft. under the road bed in edge of slough but failing to find this 1/4 post I ran North at 3960 ft. drove stake as temporary N. W. Cor. of Sec. 8 which was 32 ft. west of the stake driven as temporary N. W. Cor. of Sec. 8 per East & West runs. To be sure that I was leaving land enough in Section 7. T. 35 R. 14 E. I ran from this last temporary N. W. Cor. Sec. 8. West at 2654 ft. 1/4 post. I found standing between Sections 6 & 7. I corrected the temporary north West corner of Section 8. west six feet (6). and set a Lime Stone 27" x 18" x 7" marked IIII as the North West corner of Sec. 8. T. 35 R. 14 E. at a point 2659 ft. East of the North West corner of Section 8. I set a Lime Stone 24" x 11" x 9" marked 1/4 for the 1/4 post on the North line of Sec. 8 at a point 1329 1/2 East of the 1/4 post on the North line of Sec. 8. I set a Lime stone 22" x 9" x 8" marked X as the N. E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 1899.

M
You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 1899, I will begin a survey on Section _____ Town _____ South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

corner of the N. E. 1/4 of the N. E. 1/4 Section 8. T. 35 R. 14 E. The North East corner of Section 8 is a Sand Stone 15" x 10" x 6" marked IIII for Cor. to Sects 4, 5, 8 & 9. at a point 1312 ft. South of the N. E. Cor. of Sec. 8. I set a sand stone 24" x 9" x 6" marked X as the S. E. Corner N. E. 1/4 N. E. 1/4 Sec. 8 T. 35 R. 14 E. at a point 2624 ft. South of the N. E. corner of Section 8 and on Sec. line. I set a sand stone 20" x 9" x 4" marked 1/4 for the 1/4 post on the East line of Section 8. at a point midway between the 1/4 post on the East line of Sec. 8 and the S. E. Cor. of Sec. 8. I set a sand stone 24" x 6" x 5" marked X as N. E. Cor. S. 2 1/4 Sec. 8 T. 35 R. 14 E.

This completes the survey of Section Eight Township 35 Range 14 E. made by me. Var. 8° 15' E.
Dated at Independence Montgomery Co. Kansas. April 1. 1899.

J. L. Hibbard
Co Surveyor.

Carey Montgomery Co. Kansas. February 27th 1899.

We the undersigned solemnly swear that we have located the point within three (3) ft. of the location of the Government quarter post on the East line of Section five Township 35 Range 14 East.

Our signatures { H. H. Broome
H. B. Broome.

This is to certify that H. H. Broome & H. B. Broome appeared before me and swore to the above statement locating the point where the corner was established. Subscribed & sworn to before me this 27 day of February 1899.

J. L. Hibbard
County Surveyor.