

The Survey of Section 5 & 8 of Township 35 R. 14 E. continued. S. F. Keller & J. M. Mann, Chairmen. From the N.E. corner of Sec. 8. T. 35. R. 14 E. I ran North at 1320' drove Stake as temporary N.E. cor. Sec. 5. T. 35. R. 14 E. at 2640' drove Stake as temporary 4 post on the East line of Sec. 5. From this temporary 4 post I ran north at 2540' ft drove Stake as temporary N.E. corner of Section 5. finding this 100 ft short in measurement I examined the field notes but found they gave the East line of Section 5 as a mile in length. Feb. 24/1899 From the temporary 4 post on the East line of Sec. 5 I ran north at 1036 ft distance given from the 4 post to the Orange diminished reserve line I found the diminished reserve line to be 50 ft South of this point which would be 980 ft. north of the temporary 4 corner. I ran that the distance given by government field notes 1611 ft and found the government Stone the 15th mile post this established this line without a doubt. I found that the Stake driven as the N.E. corner of Sec. 5 was 6 ft too far north for the Township line between Townships 34 & 35 drove a stake 6 ft. South of the temporary N.E. cor. Sec. 5 as true cor to Sec 5 on Township line. The 4 post on the East line of Sec. 5 was located by two disinterested parties, who swore to the location, locating by an old hedge row planted long ago. The parties locating the 4 post on East line Sec. 5 made oath as follows. Carey, Montgomery Co. Kansas. 27/1899. we the undersigned solemnly swear that we have located the point within three (3) ft of the location of the Government quarter post on the East line of Section No (5) Twp Township 35 Range 14 East. H. B. Broome Subscribed and sworn to before me this 27 day of February 1899. S. L. Hibbard Co. Surveyor.

Set a sand Stone for 4 post on East line Sec. 5. 15" x 8" x 6" marked 4. At the North East corner of Section 5. T. 35. R. 14 E. set a line Stone 13" x 8" x 9" marked 1111 for corner to Sects 4. 5. 32 & 33. From the N.E. corner of Sec. 5 I ran West on the Township line at 1320 ft. Stone at 2640 ft. drove stake on with hedge at 5280 ft. drove stake as temporary N.W. corner of Sec. 5. From this temporary N.W. corner of Sec. 5 I ran S. 0° 30' E. at 2000 ft. off set East 60 ft on acct. of creek ran South 300 ft. off set back West to sec. line thence South on Section line 2640 ft. drove stake as temporary 4 post on West line Sec 5. From this temporary 4 post I ran South 0° 30' E. at 1263 ft. Stone at 2560 ft. Stone South West corner of Sec. 5. This making the west line Sec 5. 80 ft. Short as the distance given by Government field notes was that the 4 post on the west line of Sec. 5 was 85 ft. South of this North Side of the creek and the correction would come near this place. I located the point for the 4 post would be in a ditch. I set the witness stone marked as 4 post 25 ft. East of the true point 15" x 10" x 4" marked 4 at the North West corner Sec. 5 set a line Stone 24" x 10" x 6" marked 1111 for corners to Sections 5, 6, 31 & 32. Distance on West line North of 4 post is 2583 ft. For the 4 post on North line Section 8 set a line Stone 20" x 9" x 5" marked 4, closed for the day, until Monday February 27/1899.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

Kansas, 1899.

M. You are hereby notified that, at o'clock A. M., on the day of 1899, I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

drove stake as temporary center of Sec 5. at 2270 ft. west of temporary center Sec 5 drove Stake & quit for the night Tuesday Feb 28/1899 from the Stake driven last night at East bank of Cheyenne Creek. I ran west at 2658 ft. Section line at the point where 4 post should be from the 4 post on the North line section 5. I offset West 20 ft. on acct of hedge ran South at 2550 ft. drove stake temporary center Sec. 5. At a point 1110 ft. South 1° 15' E. North bank of creek at 1308 ft. drove Stake as temporary N.W. corner Sec. 5 at 905 ft. South 1° 15' E. from this Stake center D.M. & A. R.R. at 1328 ft. came out 22 1/2 ft west of 4 post offset back to line 20 ft. leaves 2 1/2 ft error. correction for center Sec. 5 would be 21 1/4 ft East from temporary center Sec. 5 I quit for the day and adjourned until March 2/1899 on acct of a survey on Chautauqua County line March 2/1899.

Survey of Section 5, Township 35 continued as the East line of Sec 5 is 2 1/2 ft short I corrected stake set as the N.E. cor. of Sec. 5 of Sec 5. 10° 7' South as true point for this corner. For the center of Section 5 I set a sand Stone 15" x 10" x 6" marked X X as center Sec. 5 which is 2558 1/2 ft South of the 4 post on the North line Section 5 and 2649 ft. to E. 4 post At a point 1316 1/2 ft South of the center Section 5 I set a sand Stone 24" x 10" x 5" marked 4 for N.E. cor Sec 5. From a point on the 4 line 1324 1/2 ft west of the 4 post on East line section 5 I ran South to a flag on 8 post on south line Sec 5 at 1318 ft drove stake as temporary center Sec 5. From this Stake I ran S. 0° 45' E. 10' creek 140' same creek 380' same creek 602' center D.M. & A. R.R. at 1318 ft. 4 post on South line Sec 5 For center Sec 5 set a flag Stone marked 15" x 8" x 4" marked X.

This completed the subdivision of Section 5 T. 35. R. 14 E.

Dated at Independence Montgomery Co. Kansas April 1/1899.

Var. 8° 15' E.

S. L. Hibbard.

Co. Surveyor.