

This is to certify that I L. L. Hibbard County Surveyor of Montgomery County Kansas was ordered by James Lillard to survey and subdivide Sections Thirty six, Township 32, Range 15, East. On February 27, 1899, the following named parties were notified that a survey of the above named Section would be made. Survey beginning on March 15, 1899 at 9 o'clock A.M.

Notice of Survey. A.C. Stich, J.H.C. McKinzie agts for Caledonia Investment Co., A.J. Haskell, J.M. Hurst, Sidney Lillard, E.C. Kreider, John F. Evans, Walter M. Wade, Clark Milligan, W.H. Nelson agt., H.H. Dodd, Mary B. Craig, James Lillard, A. Armstrong, Mrs. Josephine Pugh, Foster Brothers, R.D. Parkhurst, William Dunkin, Wesley Austin, C.J. Moore. Geo. L. Sursey, Leavengood & Mills. You are hereby notified that I will be at the residence of James Lillard on the 15th day of March 1899 at Nine (9) o'clock P.M. for the purpose of surveying the lands of James Lillard & others lying in Section 36 Township 32, Range 15 East. you will therefore be prepared to pay your proportionate part of the expenses of said survey in accordance with Section 7411 Chapter 39 of the laws of 1891. Dated at Independence Kansas this 27th day of Feb. 1899. L.L. Hibbard. Co. Surveyor.

On March 15, 1899, I began the survey. We went to the South East corner of Section 36, on the Range line and dug for a stone which was standing at ten years ago on a line with a ledge running East and West on South line of Section 31, T. 32, Range 15 E. Having had occasion to survey from this stone several times before this, I was disappointed in not finding it, but found a portion of the stone without doubt near by the road side. To get a starting point I went to the North East corner of Section 25, T. 32, R. 15 East and measured south on the Range line. Walter Shirey assisted me as chainman & was duly sworn. We measured south at 2640 ft. an iron pin the 4th post on the East line of Section 25. From this iron pin the 4th post on East line of Sec. 25. I ran South at 158 ft. Center S. K. Railroad at 2640 ft. drove stake as temporary North East corner of Sec. 36. From this temporary corner I ran south at 2640 ft. drove stake on East side of a ditch as the temporary 4th post on the East line of Section 36. From this temporary 4th post on the East line of Section 36. I ran South on the Range line at 1704 ft. North end of iron bridge across Rock Creek at 2440 ft. drove stake as temporary South East corner of Section 36 which was on a line of the East & West ledge on South line of Section 31, T. 32, R. 15 E. before mentioned and quit for the day and adjourned until March 17, 1899. March 17, 1899 Survey of Section 36 T. 32, R. 15 E. continued. H. Meyer to assist in chaining and was duly sworn. From a temporary N.E. corner, Sec. 36. I ran East at (this temporary corner was a stake driven on a line with the East line of the fair grounds situated in NE 1/4 Sec. 35, T. 32, R. 15 E.) 1320 ft. drove a nail in the bridge over draw at 2643 ft. drove Railroad spike as temporary 4th post on the North line of Section 36. From this temporary 4th post on the North line of Section 36 I ran East on Sec. line at 2640 1/2 ft. temporary N.E. corner of Sec. 36 driven on North & South run as it was near noon & raining we quit for the day. Adjourned to March 21, 1899. March 21, 1899. Survey of Section 36, T. 32, R. 15 E. continued from a stake temporary S.E. corner of Section 36. I ran West on the Township line at 2640 ft. a stone 4th post on South line Sec. 36 at 3960 ft. post. stone at 4040 ft. East bank Rock Creek. At 117 ft. Center U. V. & L. R.R. at 5280 ft. by cottonwood tree in ledge center of tree is about the corner. From this cottonwood tree I ran North between Sections 35 & 36 at 1321 ft. a stone 4th post at 2640 ft. drove stake temporary 4th post at 3960 ft. drove stake a temporary S.W. corner of NW 1/4 Sec. 36. at 5284 ft. stake center East & West road NW corner of Section 36. This point being true point for NW corner Sec. 36. I set an iron bar 3x3x18" as the corner. At a point 1320 3/4 ft. East of NW corner Sec. 36. I took up a plank in the bridge and drove an iron pipe as 4th post in bottom of draw, but find over it. At 2641 1/2 ft. at a line stone 17x2x3 marked 4th corner iron bar beside it for 4th post on North line of Section 36. At a point 2646 1/2 ft. east of 4th post on the North line Sec. 36 on the Range line I set a line stone 22x8x4 and an iron bar beside it 4x4x28" stone marked 1111 for corner to Secs. 25, 36, 30 & 31. March 23 set for 4th post on East line of Section 36 a line stone 16x12x6 marked 4th corner bar beside it 5x3x30" at a point 2640 ft. South of this 4th post on East line Sec. 36. I set a sand stone on the Range line & Township line stone 20x12x6 marked 1111 for corner to Secs. 36, 34, 18 & 35. I ran bar beside it 31" long. In order to establish the intermediate corners on the West line of Sec. 36. I off set East 15 ft. by putting flags at such a distance east of the Section corner. I adjusted my transit to a point between the flags at a point midway between the corners I set a line stone 20x12x6 marked 4th post on West line of Sec. 36. From this 4th post I ran East to a flag at center of Sec. 36 a stone which I found standing. at 1320 ft. drove stake as temporary S.E. corner NW 1/4 Sec. 36. at 1377' 8" center U. V. & L. R.R. at 1650 ft. draw at 2641 1/2 ft. center Sec. 36. Corrected stake at S.E. corner NW 1/4 Sec. 36. 7 inches East set a flag here for back sight corrected temporary stake 3 ft. North and set a sand stone 18x10x6 marked X with iron pin beside it as S.W. corner NW 1/4 Sec. 36. From this corner I ran East on S line at 1320 ft. drove stake as temporary S.E. corner NW 1/4 Sec. 36. From this stake I ran East at 576 ft. center U. V. & L. R.R. at 1320 ft. drove stake as temporary S.E. corner NW 1/4 Sec. 36. to determine how far East the 4th line would be from this temporary corner I set a flag. 16 ft. West of the center of Sec. 36 and a flag 16 ft. West of 4th post on North line of Section 36 ran straight line between set back East 16 ft. which made the 4th line one foot longer 2641 ft. here I set an iron bar 33x4x2 for S.E. corner NW 1/4 Sec. 36. Corrected temporary S.E. corner NW 1/4 Sec. 36 6 inches East and at a line stone 16x6x4 marked X with iron pin beside it. this stone is 52' 1" West of Center of U. V. & L. R.R. At a point 16 ft. West and 29 1/2 ft. North of the S.E. corner of the NW 1/4 Sec. 36 I set a sand stone 24x14x8 marked X as Lillard's S.E. corner and on North West line of the Public Road at a point 2637' 7" West and 29 1/2 ft. North of South East corner NW 1/4 Sec. 36 I set a sand stone 20x7x7 marked X as NW corner of Lillard tract & S.E. corner of Dodd tract. at a point 316 1/2 ft. West on the North line of the Public Road. I set a line stone 20x12x6 marked X as the corner between Dodd & Hurst tracts at a point 469 1/2 ft. North of the South East corner of the Lillard tract I set an iron bar as the North East corner of the Lillard tract. at a point 257 1/2 ft. West of this last named corner I set a sand stone 20x12x6 marked X as the corner between Lillard & Dodd tract. this stone is on the South line of Main Street continued. At a point 316 1/2 ft. West on South line of Main Street, I set an iron pin at the corner between the Dodd & Hurst tracts this pin is 316 1/2 ft. West of the NW corner of the Lillard tract eight feet 28" long one inch in diameter. At a point nine hundred & ninety ft. 991' North of the S.W. corner of the NW 1/4 Sec. 36 I set a sand stone 14x7x6 marked X as Moore's NW corner. At a point 660 ft. East of this last named corner I set a sand stone 22x8x4 as the NW corner of Hurst & Lillard NW corner. At a point 660 ft. East of the NW corner of the NW 1/4 Sec. 36 in the center of the public road I set a sand stone 17x7x7 marked X with glass around it as Moore's S.E. corner & Parkhurst's NW corner, quit for the day adjourned until March 31, 1899. Independence, March 31, 1899 from the S.E. corner NW 1/4 Sec. 36 T. 32, R. 15 E. I ran North on S line at 330 ft. drove stake at 660 ft. drove stake at 1322' 6" 4th corner under bridge, corrected the stake at 990 ft. to 991' 1/2". Drove iron pin & stone as corner to Sidney Lillard & Mills tract. Corrected 660 ft. stake to 661 1/2 ft. and set a stone 15x10x6 marked X as NW corner of Sidney Lillard tract & NW corner of Burton addition to Independence at a point 330 1/2 ft. North of S.E. corner of NW 1/4 Sec. 36 I set a sand stone 16x10x6 marked X with iron pin beside it as Parkhurst's NW corner & S.E. corner of Burton addition. At a point 463 ft. West of Sidney Lillard's NW corner and on the South line of the Mills tract I set a sand stone 20x10x6 marked X as NW corner of Lillard & S.E. corner of Hurst tract. At a point 330 1/2 ft. South of C.J. Moore's NW corner I set a sand stone 15x10x6 marked X as corner to Hurst & Leavengood's tracts. Iron pin beside it. At a point 330 1/2 ft. South last named corner I set a sand stone 15x10x6 marked X with iron pin beside it. this stone is on Moore's East line and is the corner to Leavengood's & Parkhurst's tracts & Lillard's. At a point 197 1/2 ft. East of the South West corner of the Hurst tract I set a sand stone 15x8x5 marked X as corner between Sidney Lillard & Hurst on North line of Leavengood tract. At a point 330 ft. West of Moore's NW corner I set a sand stone South West corner of Mills tract S.E. corner of O. Armstrong tract. at a point 330 ft. East and 30 ft. South of the NW corner of Sec. 36 T. 32, R. 15 E. I set a line stone on South line of Public Road as the corner between Mills & Armstrong tracts. This completed the survey.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

Kansas, 1899.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 1899, I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

Dated at Independence Montgomery Co. Kansas, April 7, 1899.

L. L. Hibbard

Var. 8° 15' E.

Co. Surveyor.