

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I, S. L. Hibbard County Surveyor of Montgomery County Kansas was ordered by H. L. Martin, Survey and Subdivide and locate corners to Lots 1, 2, 5, 6, 7, 8, 11 and 12 in Section Seven (7) Township 33, Range 17 East, On October 23rd 1899 the following named parties were notified that a Survey of the above named Sections would begin on October 31st 1899.

Mrs. J. L. Hadley
J. L. Craig
J. N. Clark
Isaac Hill
E. P. Todd
Louis Billings

William M. Googen
J. A. Heles,
H. L. Martin
Mrs. J. L. Jochman
J. H. Macon
Chas. Rozell
A. P. Stich

On October 31, 1899 I began the Survey. J. L. Hadley and Frank Koresky were selected as chainmen and were duly sworn I began at the $\frac{1}{4}$ post on the South line of Section 7, T. 33 R. 17 E. and ran west to a stake at the South West corner of Sec 7 Town and Range as above at 2640 ft. drove stake as true point for the South West corner of Lot 11 of Sec 7. here I set a lime stone 26" x 16" x 3" marked 1111 as South Cor to Lot 11 Sec 7 T. 33, R. 17. as the N. W. corner of Lot 2 of Sec. 7. As standing I put a flag at this stone and ran north to it found the distance to be 5262 ft. at a point 2631 ft. South of the N. W. corner of Lot 2 of Sec 7 T. 33, R. 17, E. I set a Lime Stone 32" x 12" x 6" marked $\frac{1}{4}$ for corner to lots 4, 5, 8 and 9, at a point 1315 $\frac{1}{2}$ ft. north of the South West corner of Lot 11, Sec 7, T. 33 R. 17, E. I set a Lime stone 20" x 10" x 3" marked $\frac{1}{8}$ for corner to Lots 8, 9, 10 & 11, of Sec 7, T. 33 R. 17, E.

From the North West corner of Lot 2 of Sec 7 T. 33 R. 17, I ran East at 2645 ft found a Stone Established $\frac{1}{4}$ post on the North line of Sec 7. From this Established $\frac{1}{4}$ post I ran South on the $\frac{1}{4}$ line to the $\frac{1}{4}$ post on the South line of Sec. 7. I found the distance to be 5243 ft and quit for the day.

November 1, 1899 continued Survey of Sec. 7 T. 33, R. 17, E. We remeasured the distance between the $\frac{1}{4}$ posts from the north line of Sec 7 to the South line of Sec 7, T. 33 R. 17. We found the distance to be 5243 ft. at a point 2621 $\frac{1}{2}$ ft. South of the $\frac{1}{4}$ post on North line of Sec 7, which is the middle point, I set a Lime stone 33" x 19" x 5" marked X as center cor or corner to Sec $\frac{1}{4}$ NE $\frac{1}{4}$ and Lots 6 and 7 of Section 7 T. 33 R. 17 E. at a point 1310 $\frac{3}{4}$ ft. North of the $\frac{1}{4}$ post on South line of Sec 7 I set a Lime Stone on the $\frac{1}{4}$ line 20" x 6" x 5" marked X as corner to lots 7 & 12 of Sec. 7 T. 33 R. 17 East. This completed the Survey on November 1, 1899

Var $8^{\circ} 05' E$.

Dated at Independence, Montgomery Co.
November 25th 1899

S. L. Hibbard

Co Surveyor.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

[Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.]

Kansas, 189...

M
You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189..., I will begin a survey on Section _____, Town _____, South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.