

This is to certify that I D. Hibbard County Surveyor of Montgomery County Kansas was ordered by William Hanson to survey and subdivide section seventeen Township 33, Range 16 East. On July 16, 1900 the following named parties were notified that a survey of the above described section would be made to begin at 10 o'clock July 25, 1900

John Barts	T. B. Clifford
B. T. Guernsey	M. D. Smith
William Horgan	A. M. Shultz
Helen Shoemaker	A. S. Parkhurst
W. McDougal	Fannie Lincott
William Hanson	Ruth Bennett
Jane Blue	Mary E. Logan
J. M. Logan	Thomas O. Riley
N. Blannett	J. M. Altafer
Dwight Allyn	Prudence Murphy

On July 25, 1900 I began the survey John Dix and Wesley Smith were selected as chainmen & were duly sworn. I went to the north east corner of section 17, T. 33 S. R. 16 E. A stone marked with four lines, Gov Marks I ran due west at 2600 ft drove stake as temporary 1/4 post on north line of sec 17 from this stake I ran west at 2553 ft drove stake in center of cross Roads as temporary north post corner sec 17. From this temporary north west corner of sec 17 I ran south at 2654 ft, drove stake in center of Road Hedge running east & west on the 1/4 line. Stopped at Altafer for dinner. From stake on west line sec 17 as 1/4 post I ran south at 2654 ft, stone south west corner of sec 17. From the south west corner of section 17, T. 33 S. R. 16 E. I ran N. 89° 10' E. at 2640 ft drove stake near center of cross Roads as temporary 1/4 post on the south line of sec 17. From this temporary 1/4 post on the south line of sec 17 I ran N. 89° 10' E. at 2682 ft a stone the south east corner of section 17, T. 33 S. R. 16 E. From the south east corner of sec 17 I ran due north to a flag on the 1/4 post on the east line of sec 17 I found the distance to 2605 ft found the 1/4 post standing & marked. From the 1/4 post on the east line of sec 17, T. 33 S. R. 16 E. I ran North 0° 30' west at 870 ft Creek Run west at 1310 ft wire fence tied cloth on fence wire for temporary 1/4 post, from this temporary 1/4 post on east line of sec 17, I ran N. 0° 30' west at 1313 ft Come out 65 ft, East of the N.E. corner of sec 17, T. 33 S. R. 16 E. Quit for the day, July 26, 1900 from the temporary 1/4 post on the west line of sec 17 which was correct I ran east on the 1/4 line at 2640 ft drove stake in Road at the top of the Hill as temporary center corner of sec 17. From this temporary center cor. I ran due east at 900 ft Ravine at 130 ft drove stake as temporary 1/4 cor at 2581 ft the 1/4 post on east line of sec 17 I corrected temporary 1/4 post 1312 ft north of 1/4 post on east line sec 17 32 1/2 ft, west, as true point for the south S.E. cor N. 1/2 N.E. 1/4 sec 17. At this point I put a flag & a pole at the N.E. corner of sec 17 Ran a straight line between at a point on this line 165 ft, south of the N.E. corner of sec 17 drove stake as temporary S.E. cor of 10 acre tract. From temporary 1/4 post on south line sec 17, I ran north on 1/4 line at 2628 ft intersected E. & W. 1/4 line at center sec 17. From this temporary center sec 17, I ran N. 1° W. at 1305 ft, stone on 1/4 line in center Road set by some surveyor at 2635 ft intersected sec line Drove stake as temporary 1/4 post - Quit for the day, July 27, 1900

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.
(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

_____, Kansas, 189____.

M. _____

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____ Town _____ South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

_____, County Surveyor,
_____, County, State of Kansas.

in center Road set by some surveyor at 2635 ft intersected sec line Drove stake as temporary 1/4 post - Quit for the day, July 27, 1900

Survey of sec 17 continued I set for 1/4 post on north line of sec 17, T. 33 S. R. 16 E. a lime stone 30" x 10" x 9" marked X this post is 2535 ft west of the north east corner of sec 17. At a point 172 ft south of the 1/4 post on the north line of sec 17 I set a lime stone 35" x 8" x 6" marked X as S.E. cor of 10 acre tract. At a point on the north line of sec 17, 1309 ft, west of the 1/4 post I set a lime stone 28" x 7" x 5" marked X as S.E. cor S.E. 1/4 Sec 8, T. 33 S. R. 17. At the North west cor sec 17 I set a lime stone 20" x 14" x 3" marked III for N.W. cor sec 17, 18, 7 & 8. For 1/4 post on west line sec 17 I set a lime stone 20" x 6" x 5" marked 1/4 at a point 1316 ft east of 1/4 post on west line sec 17 I set a sand stone 16" x 8" x 3" marked X as N.E. cor N. 1/2 N.E. 1/4 Sec 17 for 1/4 post on south line sec 17 set a lime stone 18" x 10" x 4" marked 1/4 This stone is in the center of the cross Roads (Hedges have been planted here for years & present stone was standing when Hedges were set reported by old settlers) At a point 1295 ft east of the center of sec 17 I set a lime stone 20" x 16" x 3" marked X as S.E. corner S.E. 1/4 N.E. 1/4 Sec 17 set for center sec 17 a lime stone 20" x 12" x 4" marked X measured from 1/4 stone which I found standing 80 rods north of center sec 17 East 2556 ft 1/4 post at a point midway between these 1/4 posts I set a lime stone 28" x 6" x 3" marked X as N.W. cor S.E. 1/4 N.E. 1/4 Sec 17. At a point 1311 1/2 ft north of the 1/4 post on the east line sec 17 I set a lime stone on sec line 25" x 12" x 4" marked X as S.E. cor, N.E. 1/4 N.E. 1/4 Sec 17 At a point 172 ft south on sec line from N.E. cor sec 17 I set a lime stone 30" x 12" x 5" marked X as S.E. cor of the 10 acre lot This finished the survey

Var 8° E.
Dated at Independence Montgomery Co Kansas Aug. 25, 1900
D. Hibbard Co. Surveyor.