

Geo. W. Crane & Co., Topeka, Kas.

This is to certify that I J. D. Hubbard County Surveyor of Montgomery Co Kansas was ordered by R. J. Corley, J. P. Sheffield to survey and subdivide the west half (1/2) of section Thirty Two (32) Township 34 Range 14 East, On the 6th day of December 1900. The following named parties were notified That a survey of the above named sections would be made on December 12th 1900, M. S. Pease, Joseph Kenline, Commercial Bank Mtg Co, Mr Frost A. J. J. P. Sheffield, R. J. Corley, Michael H. Fridline, Thomas M. Mann, S. F. Keller - On December 12th 1900 I began the Survey H. C. Leobb and A. A. Evans were selected as chainmen and were duly sworn. I began at the South West corner of Section 32 T. 34 R. 14 E. found part of a stone in the ground which is claimed to be part of Government corner stone which was 8 1/2 ft north and 11 ft west of a stone set on the Township line as the true corner of the Four Sections. From this portion of stone I ran north 0° 30' West at 2650' drove stake as temporary 1/4 post on West line Sec 32. From the stake I ran north 0° 30' West at 1000 ft, Cheyenne Creek at 2645' drove stake near center of cross road as temporary N. W. cor, to sec, 32, I also went to the North East corner of Sec 32, T. 34 R. 14 a stone I ran west at 2640' drove stake as temporary 1/4 post on North line sec, 32. At 52 60 ft temporary N. W. corner, corrected temporary 1/4 post north line sec 32 10 ft East which made it on a line with the old fence here I set a lime stone 22" x 10" x 4" marked 1/4 for the 1/4 post on north line section 32. For the North corner of Section 32, I set a lime stone 26" x 14" x 6" marked IIII at a point 80' north + 3 1/2 ft South on West line sec 32. I set a sand stone 20" x 12" x 5" marked X for S. West corner N. W. 1/4 section 32 T. 34 R. 14 E. For 1/4 post on West line section 32 set a lime stone 20" x 10" x 6" marked 1/4. From this 1/4 post I ran East to 1/4 post on East line sec, came out 14 ft North of 1/4 post, for center section correction would be 7 ft south, made this correction. From a flag 10 ft west of 1/4 post on South line of Section 32 I ran north to 1/4 post on North line sec 32. At the intersection of 1/4 lines set a lime stone, 22" x 10" x 4" marked X as center of section 32 measured north on 1/4 line from this stone 2645 ft to 1/4 post, divided the distance and set a lime stone on 1/4 line 1322 1/2 ft north of the center of section 32. This completed the survey -

Var 8° E.

Dated at Independence Dec 29, 1900

J. D. Hubbard

Co Surveyor.

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. BAILEY, Topeka, Kansas.)

Kansas, 189.....

M

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.