

Survey No. , Section 10 , Town 33 South, Range 14

This is to certify that S. P. Hibbard, County Surveyor of Montgomery County, Kansas was ordered by Emma S. Welden to Survey and subdivide Section Number 10, Township 33, Range 14 East, the following named parties were notified that a Survey of the above named Section would be made on January 23rd 1901 to begin at 10 o'clock A.M. Notice sent January 14th 1901

Henry S. Goff	William Pilgrim
William S. Hodges	J. B. Rea
S. H. Tucker	Nellie A. Jones
William Tucker	Emma S. Welden
Elizabeth C. Davis	Sarah Shousey
Henry A. Hisey	William Haisch
James Morrison	Chas. Morris
Eldridge H. Moon	Elmer Demott.
Geo. H. Morris	

On January 23rd 1901 I began the Survey A. B. Page & J. N. Patton were selected as chainmen & were duly sworn, I found a small portion of the old Government Stone at the North East Corner of Section 10 T. 33 R. 14 E. I set in its place a lime stone 26" x 12" x 6" Marked 1111 for the corner of Sections 2, 3, 10 & 11. From this established corner the old government stone beside it, I ran South 1' East at 1320 ft drove stake as temporary S.E. corner of the N. 1/2 S.E. 1/4 Section 10 at 2640 drove stake as temporary 1/4 post at 3960 feet drove stake as temporary S.E. corner N. 1/2 S.E. 1/4 Section 10, at 5280 ft drove stake as temporary South East Corner of Section 10 To prove this point I went east 80 rods a stone S.E. cor. S. 1/4 S.E. 1/4 Sec 11 I ran West at 1320 ft. drove stake which was 10 feet west & 4 feet south of the stake set as temporary S.E. cor. from the North 1/2 of South run From this last driven stake I ran west on the South line of Section 10 at 1320 ft a stone as S.E. cor. S. 1/4 S.E. 1/4 Sec 10, at 2640 feet drove stake as temporary 1/4 post on the South line Section 10 at 5280 ft. stone South West cor. Section 10, From S.W. cor. section 10, I ran north 1' West at 1320 drove stake at 2641 ft a stone 1/4 post on West line section 10, From this stone I ran north at 1320 ft. drove stake at 2641 ft. stone North West cor. section 10, from this stone I ran East on North line Section 10, at 2636 ft. stone 1/4 post on North line Sec 10. From this 1/4 post I ran East at 2637 1/2 ft Stone N.E. cor. Section 10 I quit for the day. Feb 24th 1901 Set a flag on the South West corner of Sec 10, T. 33, R. 14 E. also on 1/4 post adjusted my transit on straight line set flag at 1/4 post on South line Sec 10, at S.E. corner Sec 10 Set a lime stone 16" x 14" x 3" Marked 1111, For 1/4 post on East line Section 10 located South 2 ft, 3/4 Set a lime stone 24" x 8" x 3" Marked 1/4, At a point 1321 ft north of the South East corner Sec 10 Set a Lime Stone 24" x 16" x 3" Marked X for N.E. corner S.E. 1/4 S.E. 1/4 Sec 10, T. 33, R. 14 E.

NOTICE—Surveyor's Permanent Record, State of Kansas.

[Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.]

[Copyright, 1891, by B. A. Bailey, Topeka, Kansas.]

Kansas, 189.....

M.....

You are hereby notified that, at o'clock A. M., on the day of 189....., I will begin a survey on Section Town South, Range in which you are interested, and shall continue the same from day to day until completed. Commencing at the corner of said Section, I shall permanently establish

County Surveyor,

County, State of Kansas.

26" x 6" x 3" Marked X as the center of section 10. I measured north from the center Sec 10, 2638 ft. 1/4 post on North line Section 10. I divided the distance & at a point 1319 ft. on the 1/4 line South of the 1/4 post on the northern section 10. Set a lime stone 22" x 10" x 3" marked X as S.W. corner, N. 1/2, N.E. 1/4, Sec. 10 T. 33 R. 14 East. This completes the survey on Jan 24, 1901.

Var. S. 8° E.

Dated at Independence Montgomery Co Kansas Feb 9th 1901.

S. P. Hibbard, Co. Surveyor.