

This is to certify that I, S. D. Hibbard, County Surveyor of Montgomery County, Kansas, was ordered by Noah Laughlin to survey & subdivide Section Seventeen (17) Township 32 Range Fourteen (14) East, January 22, 1901. The following named parties were notified that a survey would be made of the above described Section to begin on January 29, 1901.

M. F. Kopf	A. J. Hancock
J. H. Reid	A. B. Stick
Marcus C. Ford	E. B. Morrell
H. C. Newkirk	H. H. Miller
O. T. Hayward	Richard E. Laughlin
Thomas Newkirk	John H. Deer
M. A. Newkirk	Jonathan T. Doyle
J. H. Goodwin	Edward Austin
Joseph J. Vance	H. H. Frost Aft
Philadelphia Mtge Co.	New England Trust Co.

On Jan 29, 1901, I began the survey of Section 17, Township 32, R. 14 E. Alvaro Newkirk & Henry Mikel were selected as chainmen and A. D. Newkirk as flagman who were duly sworn. From the south west corner Sec 17, T. 32, R. 14 E. a stone ran North at 2187 feet top bluff South side Elk River 2250' center dry bed Elk River 2435' ft, water edge Elk River at 2654' Stone 1/4 post which was in dispute. From this Stone I offset 100' East ran North 30' at 2640' ft drove stake 100' West on true line as temporary N. W. cor, sec, 17. I checked from Hedge Fence said to be on 1/4 line running N. & S. on North line sec 17, T. 32, R. 14 E. Did not find 1/4 post but it had been in hedge East 2660' come out South of temporary N. W. cor, sec 17, but on same line N. & S. I then went to the N. W. corner sec 8 T. 32, R. 14 E. I ran South 2640' ft, I found a line stone in several parts - (broken) but setting on End of seemed to be set for Sec. 17, quit for day. Jan 30, 1901. From the S. W. cor sec 17, T. 32, R. 14 E. I ran S. 89° 8' at 1100' ft, draw at 2657' ft, Stone 1/4 Post. From this 1/4 post I ran S. 89° 8' at 2650' Stone South East cor, sec 17. From S. E. cor sec 17 I ran N. 0° 45' W. at 2662' ft Stone 1/4 post. From this 1/4 post I ran N. 0° 45' W. at 2653' found a portion small line stone supposed to be N. E. cor sec 17. From this point I ran S. 89° 40' W. at 1100' ft, water edge Elk River at 2726' ft grave yard. N. W. corner said by several land owners there to be where 1/4 post on North line sec 17 stood. From this point I ran S. 89° 10' W. at 2683' ft come out at supposed cor stone N. E. cor, sec 17. Here I set a line stone 20" x 17" x 6" marked III also set part of old government stone beside it as the N. E. cor, sec 17, T. 32, R. 14 E. at a point 645 1/2' West of the 1/4 post on the North line sec 17 set sand stone 24" x 10" x 6" marked X as the N. E. cor 6 1/2' of the 6 1/2' N. W. 1/4 sec 17, T. 32, R. 14 E. For 1/4 post on North line sec 17 drove iron pin 34" x 1 1/2" x 3/4". From the center sec 17 a stone ran N. 89° 15' W. 655' ft, marked Elm tree to bearing N. 0° 45' W. on North bank Elk River drove stake Elm tree S. E. cor, 6 1/2' N. W. 1/4 sec 17, at 920' ft Elk River 1020' ft West side Elk River top bank at 1950' ft. bank Elk River at 2626' ft 1/4 post. This 1/4 post was set by me about six years ago but no record made at that time as parties wanted me. Locate it at that time by witness trees the stumps we found at that time the 1/4 post being a small stone I set a line stone 34" x 8" x 5" marked 4. This Stone is 2658' ft, N. 0° 45' W. of the South West corner Section 17, T. 32, R. 14 E. at a point on the West line on the North bank of Elk River 6 1/2' N. W. 1/4 sec 17, T. 32, R. 14 E. set a line stone 26" x 12" x 4" marked X as witness cor, true cor. being in dry bed of Elk River, south of water. At the North East corner Section 17, T. 32, R. 14 E. set a line stone 15" x 16" x 3" marked IIII put part of old Gov stone by it as witness to same. This finished survey

NOTICE—Surveyor's Permanent Record, State of Kansas.

Geo. W. Crane & Co., Printers and Binders, Topeka, Kas.
Blank Books and Legal Blanks of Every Description.

(Copyright, 1891, by B. A. Bailey, Topeka, Kansas.)

189.

You are hereby notified that, at _____ o'clock A. M., on the _____ day of _____, 189____, I will begin a survey on Section _____ Town _____ South, Range _____, in which you are interested, and shall continue the same from day to day until completed. Commencing at the _____ corner of said Section, I shall permanently establish _____

County Surveyor,

County, State of Kansas.

17, T. 32, R. 14 E. at a point on the West line on the North bank of Elk River 6 1/2' N. W. 1/4 sec 17, T. 32, R. 14 E. set a line stone 26" x 12" x 4" marked X as witness cor, true cor. being in dry bed of Elk River, south of water. At the North East corner Section 17, T. 32, R. 14 E. set a line stone 15" x 16" x 3" marked IIII put part of old Gov stone by it as witness to same. This finished survey

Car 8° 8'

Dated at Independence Montgomery County Kansas, February 23, 1901.
S. D. Hibbard, Co. Surveyor.